

July 2020

Bureau of Waste Site Cleanup Southeast Regional Office Massachusetts Department of Environmental Protection C/o Angela Gallagher Site Remediation Section 20 Riverside Drive Lakeville, MA 02347

RE: Immediate Response Action Status and Remedial Monitoring Report #41

Barnstable County Fire Training Academy FTA Facility

155 South Flint Rock Road Hyannis, Massachusetts DEP Release Tracking No. 4-26179

Project Number #6206

Dear Ms. Gallagher:

BETA Group, Inc. (BETA) has prepared this Immediate Response Action (IRA) Status and Remedial Monitoring Report (RMR) for the Disposal Site (the Site) referenced as the Barnstable Country Fire Training Academy (the FTA Facility) located at 155 South Flint Rock Road in Hyannis, MA on the behalf of Barnstable County. This report was completed on behalf of Barnstable County and in accordance with Massachusetts Contingency Plan (MCP) - 310 CMR 40.0000.

This is the 41st monthly IRA RMR Status report. It documents the IRA/RMR activities being conducted to address a release of PFOS/PFOA to groundwater, soils, surface water, and sediments located at the Site. A potential Imminent Hazard (IH) condition and Condition of Substantial Release Migration were previously identified at the Site. This letter report specifically addresses the status of the Site groundwater pumping and treatment systems (GWPTS) during the monthly reporting period from April 1 to April 30, 2020.

The completed BWSC105 Immediate Response Action (IRA) Transmittal Form and attached BWSC105A and BWSC105B IRA Remedial Monitoring Report Forms are being submitted to the MassDEP electronically via the eDEP system. This letter is being submitted to the Massachusetts Department of Environmental Protection (MassDEP) as an attachment to those forms. Copies of these forms prior to electronic signature are included as Attachment A.

REMEDIAL MONITORING REPORT – APRIL 2020

During the April 2020 reporting period, the primary treatment system (GWTS #1) and secondary system (GWTS #2) were in operation for all or portions of approximately 30 days. There was one scheduled shutdown during this reporting period for GWTS #1 and GWTS #2; the systems were shut down on April 9, 2020 for several hours while Global Cycle pumped out the accumulated iron-oxide sediments from both equalization (EQ) tanks. Additionally, backwashes were conducted on the primary LGAC vessels of both GWTS #1 and GWTS #2 on April 9, 2020. On April 28, 2020, BETA collected performance samples from both GWTS #1 and GWTS #2 systems, which were both in operation at the time of sample collection.

Health Advisories and Regulatory Standards Used for Comparison

During the initial two years of the GWPTS operation (July 2016 through June 2018), the USEPA revised Health Advisory (HA) of 0.070 μ g/L for two PFAS chemicals, Perfluorooctanoic acid (PFOA) and Perfluorooctanesulfonic acid (PFOS), was used for comparison to the analytical results of GWPTS performance samples. The HA (revised downward to 0.070 μ g/L in July 2016) applied to each compound individually or for the total concentration of the two. Subsequently, MassDEP adopted the USEPA HA. The USEPA considers its HA to still be in effect (as of March 2020). However, for MCP purposes it has been superseded by MassDEP guidelines and regulatory actions.

On June 11, 2018, MassDEP's Office of Research and Standards (ORS) issued an updated ORS Guideline/HA that applied to the individual concentrations or the total summed of five PFAS chemicals: PFOS, PFOA, Perfluorononanoic Acid (PFNA), Perfluorohexanesulfonic Acid (PFHxS), and Perfluoroheptanoic Acid (PFHpA). From June 11, 2018 until December 2019, individual concentrations of any of these five compounds or the total concentrations of all were compared to the MassDEP ORS HA of $0.070\,\mu\text{g/L}$.

On April 19, 2019, MassDEP released the Public Comment Draft of proposed revisions to the MCP, which included proposed Method 1 groundwater risk standards for the five PFAS compounds, plus an additional PFAS compound, Perfluorodecanoic Acid (PFDA). A Method 1 GW-1 risk standard of 0.020 µg/L was proposed for the individual concentrations of any of these six compounds or the total concentrations of all six. From May 2019 through the current reporting period, tabulated treatment system analytical results have been compared to all six PFAS compounds of concern for informational purposes.

In December 2019, MassDEP published final MCP Method 1 risk standards for PFAS with an effective implementation date of December 27, 2019. The final MCP PFAS risk standards for groundwater include the 6 PFAS compounds of concern listed above and a $0.020\,\mu g/L^1\,GW-1$ numerical risk standard. These MCP risk standards are included in Table 1A and Table 1B. The total PFAS concentrations reported and discussed for comparison purposes in this report are based on the six regulated PFAS compounds included in the final MCP risk standards of December 27, 2019.

 $^{^1}$ Concentrations of PFAS are presented in the data tables of this report in nanograms per liter (ng/L), also referred to as parts per trillion (ppt), and are reported by the laboratory in those units. However the published MCP Method GW-1 numerical risk standards are in presented in or micrograms per liter (μ g/L), also referred to as parts per billion (ppb). In the relevant sections of this report, both results are shown in both units.

<u>GWTS # 1 System Monitoring Results</u>

As noted, system samples were collected on April 28, 2020 from the Influent (PRW-4), Midpoint and Effluent ports and were submitted to Bureau Veritas Laboratories (formerly Maxxam Analytics) of Mississauga, Ontario (Bureau Veritas) for the laboratory analysis of Total PFAs via USEPA Method 537 M.

١

The total sum of the six Massachusetts regulated PFAS concentrations in the Influent (PRW-4) sample was 2,302 ng/L (2.302 μ g/L), well above the GW-1 risk standards. All six individually regulated PFAS compounds were detected at concentrations exceeding the new MCP GW-1 risk standard (0.020 μ g/l). Refer to the attached Table 1A, for a summary of the GWTS #1 PFAS analytical data. Recovery well PRW-4 is the source of the Influent groundwater. Based on the splitting of flow from PRW-4 to both groundwater treatment systems, the Influent analytical results apply to GWTS #2, as well as GWTS #1.

The six MA regulated PFAS compounds were detected above the laboratory reporting detection limits in the Midpoint sample, and the PFOS compound was above the MCP Method 1 GW-1 standard. For the purposes of achieving the lowest MDLs and RDLs ²(for comparison to the new MCP Method 1 Groundwater standards, Bureau Veritas reports the results for 21 PFAS compounds, including two (2) PFAS precursors; this allows the laboratory to achieve RDLs as low as 0.18 ng/L. The complete laboratory report is attached in Appendix B. The laboratory report provides details of MDLs and RDLs for each PFAS compound included in the analyte list.

Although, the six regulated PFAS compounds were detected in the Midpoint Sample, none of the six MCP regulated PFAS compounds were detected at concentrations above MDLs in the Effluent sample from System #1; in addition, the remaining 15 PFAS compounds are reported below the laboratory RDLs and MDLs, with the exception of one unregulated PFAS compound (PFHxA). The detected concentration of PFHxA (0.95 ng/L) is below the applicable Method 1 GW-1 standards (20 ng/L); however, this compound is not regulated by either Massachusetts State or USEPA. Refer to the attached Table 1A, for a summary of the GWTS #1 PFAS analytical data in the Midpoint and Effluent samples. The complete laboratory report is attached in Appendix B.

GWTS #1 Operational Details

The attached Table 2A presents the GWTS #1 performance data. For the April 2020 reporting period, the overall (average) system flow rate and gallons of groundwater treated are based on the effluent flow meter/totalizer readings reported for the system by the O&M contractor. On this basis, approximately 0.46 million gallons of groundwater were treated during the April 2020 reporting period, at an average effluent flow rate of 10.8 gpm. Based on 0.46 million gallons treated and total influent concentration of 2,302 ng/L (April 28, 2020 sample results), approximately 0.004 kilograms of PFAS were estimated to have been removed from the plume area during this reporting period.

The estimated, instantaneous combined influent flow rates (for both systems) ranged from approximately 19.2 gpm to 41.5 gpm; typically, the combined estimated instantaneous influent flow rate has been over 20 gpm.

² Method Detection Limits and Reportable Detection Limits.

As detailed in the IRA Status and RMR reports from the previous 2020 reporting periods, iron-oxide sediment has significantly accumulated in the equalization (EQ) tank and has caused a decrease in the observed system flow rates due to suspected accumulation in the force main piping and potentially in the recovery well PRW-4.

As previously noted, on April 9, 2020 Global Cycle was on Site and removed approximately 2,989 gallons of iron-oxide sediment and water from the EQ tanks of both systems and the exterior totes; following the backwash of the primary liquid-phase granular activated carbon (LGAC) vessel in GWTS #1, the observed average effluent flow rate increased by approximately 50% (during the next monitoring event). See Table 2A for details.

Due to the method used to estimate the instantaneous influent flow rate (timing of rise of groundwater in the GWTS #1 Equalization Tank with <u>both</u> force mains discharging to it), the estimated influent flow rates noted above apply to both systems, combined. Therefore, during the normal mode of operation, with the flow from each force main flowing to only one system, it is assumed that roughly 50% of the instantaneous influent rates stated above actually discharge to GWTS #1; the assumed 50% values are tabulated – (the influent flow rate for GWTS #1 is approximately 15.2 gpm). Table 2A presents the details for GWTS #1.

GWTS # 2 Monitoring Results

As previously mentioned, BETA collected performance samples from GWTS #2 system on April 28, 2020 Samples collected from the Influent (PRW-4), Midpoint, and Effluent ports were submitted to Bureau Veritas for the laboratory analysis of Total PFAS via USEPA Method 537 M. As noted above, recovery well PRW-4 is the source of the Influent groundwater to both groundwater treatment systems. Therefore, the Influent analytical results apply to GWTS #2, as well as GWTS #1.

As previously mentioned, the tabulated treatment system analytical results from GWTS #2 have been reported and compared to all six regulated PFAS compounds and their respective MCP Method 1 GW-1 Standards. The total sum of the six PFAS concentrations in the Influent sample was 2, 302 ng/L, well above the GW-1 risk standards. All six individually regulated PFAS compounds were detected at concentrations exceeding the new MCP GW-1 risk standard (0.020 μ g/l or 20 ng/L). Refer to the attached Table 1B for a summary of the GWTS #2 PFAS analytical data. The complete laboratory report is attached in Appendix B.

PFAS concentrations were detected above the RDLs or MDLs in this April 2020 Midpoint sample except for the PFOS compound – the PFOS concentration detected in the Midpoint sample was above the applicable MCP GW-1 risk standards. For the purposes of achieving the lowest MDLs and RDLs (for comparison to the new MCP Method 1 Groundwater standards, Bureau Veritas reports the results for 21 PFAS compounds, including two (2) PFAS precursors; this allows the laboratory to achieve RDLs as low as 0.18 ng/L (ppt). Laboratory analytical details are included in Table 1B and the laboratory report (in Appendix B).

Although, the six regulated PFAS compounds were detected in the Midpoint Sample, just the PFOS compound was detected at concentrations above MDLs in the Effluent sample from System #2. However, these PFOS detections was below the applicable Method 1 GW-1 standards.

The remaining 15 PFAS compounds were reported below the laboratory RDLs and MDLs. Laboratory analytical details are included in Table 1B and the laboratory report is included in Appendix B).

GWTS #2 Operational Details

For the April 2020 reporting period, effluent flow rates and influent flow rates observed have been lower than the system's optimum performance as documented during the previous 2020 reporting period. This decrease is assumed to be attributable to the iron-oxide sediment that accumulated in the EQ holding tank and was carrying over into the bag filters. In addition, precipitated iron was suspected of accumulating in the LGAC vessels. The system was shutdown on April 9, 2020 for a backwash of the primary LGAC vessel and to vacuum out the accumulated iron-oxide sediments from the system's EQ tank to help remedy the continued pressure increases. The system was shut down for approximately four hours.

The overall (average) system flow rate and gallons of groundwater treated were based on the Effluent flow rate/net totalizer readings reported for the system by the O&M contractor; approximately 0.55 million gallons of groundwater were estimated to be treated during the March 2020 reporting period, at an approximate average effluent flow rate of 13.0 gpm. Based on 0.55 million gallons treated, approximately 0.005 kilograms of PFAS were estimated to have been removed from the plume area during this reporting period. Refer to Table 2B.

As described in previous sections, during the normal mode of operation, with the flow from each force main flowing to only one system, it is assumed that roughly 50% of the instantaneous influent rates discussed above for GWTS #1 actually discharge to GWTS #2. Refer to the attached Table 2B for a summary of the GWPTS performance details.

GROUNDWATER TREATMENT PUMPING AND TREATMENT SUMMARY

During the April 2020 reporting period, the two treatment systems, GWTS #1 and GWTS #2, were in operation for all or portions of approximately 30 days. The overall (average) system flow rate and gallons of groundwater treated are based on the available Effluent flow totalizer readings reported for both systems by the O&M contractor. For the period of April 1 to April 30, 2020 both systems treated an approximate combined 1.01 million gallons of groundwater from the downgradient recovery well PRW-4 at an average, total (of the two systems) effluent flow rate of 23.8 gpm. Based on the total 1.01 million gallons treated, approximately 0.009 kilograms of PFAS were estimated to have been removed from the plume area.

Ongoing IRA Activities

Sampling results, system performance, and additional assessment work related to the ongoing response actions, such as system improvement and enhancement details, will be presented in the next IRA Status and RMR Report for the May 2020 reporting period.

Public Involvement Activities

A copy of the municipal notification to the Barnstable Town Manager, with copies to other town officials, is included as Appendix C.

The Site has been designated a Public Involvement Plan Site under the MCP. The Draft Public Involvement Plan (PIP) was presented at a public meeting held at the Barnstable Town Hall on May 2, 2019. Following the end of the comment period, the PIP was finalized and filed with MassDEP on June 30, 2019. In accordance with the final PIP, a copy of this status report will be placed in the public repository. The report will be available on-line via the County website.

Sincerely,

BETA Group, Inc.

Mykel Mendes Environmental Engineer

Mypelod Chandos

Roger Thibault, P.E., LSP Senior Environmental Engineer

Bu P. Thilo

Copy: Jack Yunits, Barnstable County Administrator

Steve Tebo, Assistant County Administrator

Attachments:

TABLES:

Table 1A – Summary of Groundwater Pump and Treatment System PFAS Analytical Data – System #1 Table 1B - Summary of Groundwater Pump and Treatment System PFAS Analytical Data – System #2 Table 2A - Summary of Groundwater Pump and Treatment System Operating and Maintenance Data-System #1

Table 2B- Summary of Groundwater Pump and Treatment System Operating and Maintenance Data-System #2

APPENDICES:

A: BWSC 105, 105A, 105B Forms

B: Laboratory Reports

C: Municipal Notification Letter to Town Manager



A. SITE LOCATION:

Massachusetts Department of Environmental Protection Bureau of Waste Site Cleanup

BWSC 105

Release Tracking Number

4 - 26179

Immediate Response Action (IRA) Transmittal Form Pursuant to 310 CMR 40.0424 - 40.0427 (Subpart D)

1. F	Release Name/Location	on Aid: E	BARNSTABLE COUNTY FIRE	TRAINING ACADEMY	
2. 8	Street Address:	155 SOUTH	FLINT ROCK ROAD		
3. 0	City/Town:	BARNSTABI	.E	4. Zip Cod	e: 026300000
Г	5. Check here if this	location is A	dequately Regulated, pursu	ant to 310 CMR 40.0110-0114	
	a. CERCLA	□ b.	HSWA Corrective Action	c. Solid Waste Man	agement
	d. RCRA State	Program (210	C Facilities)		
			OTO: (check all that ap Vritten Plan (if previously s		
Г	2. Submit an Initial I	IRA Plan.			
Г	3. Submit a Modified	I RA Plan of	a previously submitted wr	ritten IRA Plan.	
Г	4. Submit an Immine	ent Hazard E	valuation. (check one)		
	a. An Imminent l	Hazard exists	s in connection with this Re	elease or Threat of Release.	
	□ b. An Imminent	Hazard does	not exist in connection wit	th this Release or Threat of Rel	ease.
	c. It is unknown activities will be une		mminent Hazard exists in	connection with this Release of	Threat of Release, and further assessment
			mminent Hazard exists in at could pose an Imminent		Threat of Release. However, response actions
Г	5. Submit a request	to Terminate	e an Active Remedial Syste	em or Response Action(s) Take	n to Address an Imminent Hazard.
V	6. Submit an IRA Sta	atus Report			
V	7. Submit a Remedia	al Monitoring	g Report. (This report can	only be submitted through eDE	P.)
	a. Type of Report: (check one)	i. Initial Report	▼ ii. Interim Report	□ iii. Final Report
	b. Frequency of Sub	omittal: (chec	k all that apply)		
	▼ i. A Remedial M	onitoring Re	port(s) submitted monthly	to address an Imminent Hazard	
	□ii. A Remedial M	Ionitoring R	eport(s) submitted monthly	to address a Condition of Sub	stantial Release Migration.
	□ iii. A Remedial N	Monitoring R	eport(s) submitted every si	x months, concurrent with an I	RA Status Report.
	□ iv. A Remedial N	Monitoring R	eport(s) submitted annually	y, concurrent with an IRA Statu	is Report.
	c. Number of Remed	dial Systems	and/or Monitoring Program	ms: 2	
	A separate BWSC10 addressed by this tra			must be filled out for each Ren	nedial System and/or Monitoring Program

Revised: 11/14/2013 Page 1 of 6



Immediate Response Action (IRA) Transmittal FormPursuant to 310 CMR 40.0424 - 40.0427 (Subpart D)

BWSC 105

Release Tracking Number

CCIC	use	11	acking i vario	١
4	-		26179	

8. Submit an IRA Completion Statement .	
a. Check here if future response actions addressing this Release of the Response Actions planned or ongoing at a Site that has alread (RTN)	or Threat of Release notification condition will be conducted as part ly been Tier Classified under a different Release Tracking Number
b. Provide Release Tracking Number of Tier Classified Site (Prima	ary RTN):
These additional response actions must occur according to the deadl making all future submittals for the site unless specifically relating t	
9. Submit a Revised IRA Completion Statement .	
10. Submit a Plan for the Application of Remedial Additives near a se	ensitive receptor, pursuant to 310 CMR 40.0046(3).
(All sections of this transmittal form must be	filled out unless otherwise noted above)
C. RELEASE OR THREAT OF RELEASE CONDITIONS THAT	WARRANT IRA:
1. Media Impacted and Receptors Affected: (check all that apply)	☐ a. Paved Surface ☐ b. Basement ☐ c. School
▼ d. Public Water Supply ▼ e. Surface Water ▼ f. Zone 2	☐ g. Private Well ☐ h. Residence ☑ i. Soil
▼ j. Groundwater	d \square m. Storm Drain \square n. Indoor Air \square o. Air
□ p. Soil Gas □ q. Sub-Slab Soil Gas □ r. Critical	Exposure Pathway
r. Others Specify:	
2. Sources of the Release or TOR: (check all that apply)	a. Transformer
□ d. OHM Delivery □ e. AST □ f. Drums	☐ g. Tanker Truck ☐ h. Hose ☐ i. Line
□j. UST Describe:	k. Vehicle
☐ m. Unknown	
3. Type of Release or TOR: (check all that apply) $\hfill\Box$ a. Dumping	□ b. Fire □ c. AST Removal □ d. Overfill
☐ e. Rupture ☐ f. Vehicle Accident ☐ g. Leak	\square h. Spill \square i. Test failure \square j. TOR Only
☐ k. UST Removal Describe:	
☐ 1. Unknown	
4. Identify Oils and Hazardous Materials Released: (check all that apply)	a. Oils b. Chlorinated Solvents
c. Heavy Metals d. Others Specify: PFAS	
D. DESCRIPTION OF RESPONSE ACTIONS: (check all that apply	y, for volumes list cumulative amounts)
▼ 1. Assessment and/or Monitoring Only	▼ 2. Temporary Covers or Caps
☐ 3. Deployment of Absorbent or Containment Materials	4. Temporary Water Supplies
☐ 5. Structure Venting System/HVAC Modification System	6. Temporary Evacuation or Relocation of Residents
7. Product or NAPL Recovery	☐ 8. Fencing and Sign Posting
▼ 9. Groundwater Treatment Systems	☐ 10. Soil Vapor Extraction
☐ 11. Remedial Additives	☐ 12. Air Sparging
☐ 13. Active Exposure Pathway Mitigation System	☐ 14. Passive Exposure Pathway Mitigation System

Revised: 11/14/2013 Page 2 of 6



Describe:

Massachusetts Department of Environmental Protection Bureau of Waste Site Cleanup

BWSC 105

Immediate Response Action (IRA) Transmittal Form Pursuant to 310 CMR 40.0424 - 40.0427 (Subpart D)

Release Tracking Number 26179

D. I	DES	CRIPTION OF RESP	ONSE ACTIO	NS:	(cont.)				
V	15.	Excavation of Contamina	ted Soils.						
		a. Re-use, Recycling or	Treatment		i. On Site	Estimated	volume in cubic yards		
					ii. Off Site	Estimated	volume in cubic yards		
		iia. Receiving Facility:				Town:		Sta	te:
		iib. Receiving Facility:				Town:		Sta	te:
		iii. Describe:							
		b. Store		Г	i. On Site	Estimated	volume in cubic yards		
					ii. Off Site	Estimated	volume in cubic yards		
		iia. Receiving Facility:				Town:		Sta	te:
		iib. Receiving Facility:				Town:		Sta	te:
	<u>~</u>	c. Landfill		Г	i. Cover	Estimated	volume in cubic yards		
		Receiving Facility:				Town:		Sta	te:
				V	ii. Disposal	Estimated	volume in cubic yards	200	
		Receiving Facility:	TAUNTON LANDF	FILL		Town:	TAUNTON	Sta	te: MA
Г	16.	Removal of Drums, Tank	s, or Containers:						
		a. Describe Quantity and	d Amount:						
		b. Receiving Facility:				Town:		Sta	te:
		c. Receiving Facility:				Town:		Sta	te:
Г	17.	Removal of Other Contan	ninated Media:						
		a. Specify Type and Volu	ıme:						
Г	18.	Other Response Actions:	·						
		Describe:							
Г	19.	Use of Innovative Techno	ologies:						

Revised: 11/14/2013 Page 3 of 6



Immediate Response Action (IRA) Transmittal Form Pursuant to 310 CMR 40.0424 - 40.0427 (Subpart D)

BWSC 105

Release Tracking Number

- 26179

E. LSP SIGNATURE AND STAMP:

I attest under the pains and penalties of perjury that I have personally examined and am familiar with this transmittal form, including any and all documents accompanying this submittal. In my professional opinion and judgment based upon application of (i) the standard of care in 309 CMR 4.02(1), (ii) the applicable provisions of 309 CMR 4.02(2) and (3), and 309 CMR 4.03(2), and (iii) the provisions of 309 CMR 4.03(3), to the best of my knowledge, information and belief,

- > if Section B of this form indicates that an **Immediate Response Action Plan** is being submitted, the response action(s) that is(are) the subject of this submittal (i) has (have) been developed in accordance with the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000, (ii) is(are) appropriate and reasonable to accomplish thepurposes of such response action(s) as set forth in the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000 and (iii) complies(y) with the identified provisions of all orders, permits, and approvals identified in this submittal;
- > if Section B of this form indicates that an **Imminent Hazard Evaluation** is being submitted, this Imminent Hazard Evaluation was developed in accordance with the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000, and the assessment activity(ies) undertaken to support this Imminent Hazard Evaluation comply(ies) with the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000;
- > if Section B of this form indicates that an **Immediate Response Action Status Report** and/or a **Remedial Monitoring Report** is(are) being submitted, the response action(s) that is (are) the subject of this submittal (i) is (are) being implemented in accordance with the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000,(ii) is (are) appropriate and reasonable to accomplish the purposes of such response action(s) as set forth in the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000 and (iii) comply(ies) with the identified provisions of all orders, permits, and approvals identified in this submittal;
- > if Section B of this form indicates that an **Immediate Response Action Completion Statement** or a request to **Terminate an Active Remedial System or Response Action(s) Taken to Address an Imminent Hazard** is being submitted, the response action(s) that is(are) the subject of this submittal (i) has (have) been developed and implemented in accordance with the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000, (ii) is(are) appropriate and reasonable to accomplish the purposes of such response action(s) as set forth in the applicable provisions of M.G.L. c. 21E and 310 CMR 40.0000 and (iii) comply(ies) with the identified provisions of all orders, permits, and approvals identified in this submittal.

I am aware that significant penalties may result, including, but not limited to, possible fines and imprisonment, if I submit information which I know to be false, inaccurate or materially incomplete.

1. LSP #: <u>144</u>	3					
2. First Name:	ROGER P		3. Last Name:	THIBAULT		
4. Telephone:	508-331-2700	5. Ext:		6. Email:		
7. Signature:						
8. Date:		(mn	n/dd/yyyy)		9. LSP Stamp:	

Revised: 11/14/2013 Page 4 of 6



BWSC 105

Immediate Response Action (IRA) Transmittal FormPursuant to 310 CMR 40.0424 - 40.0427 (Subpart D)

Kele	ase	I racking Numbe
4	-	26179

F. PERSON UNDERTA	AKING IRA:		
1. Check all that apply:	a. change in contact name	☐ b. change of address	c. change in the person undertaking response actions
2. Name of Organization:	BARNSTABLE COUNTY COMMISSION	ONERS	
3. Contact First Name:	JACK	4. Last Name: YUNITS	
5. Street: 3195 MAIN ST		6. Title:	
7. City/Town: BARNSTA	BLE	8. State: M	9. Zip Code: 026301105
10. Telephone: 508-375	-6643 11. Ext:	12. Email:	JYUNITS@BARNSTABLECOUNTY.ORG
G. RELATIONSHIP TO	O RELEASE OR THREAT OF R	ELEASE OF PERSON U	INDERTAKING IRA:
Check here to change	e relationship		
▼ 1. RP or PRP	■ a. Owner □ b. Ope	erator	rator
e. Other RP or PR	P Specify Relationship):	
2. Fiduciary, Secured	Lender or Municipality with Exemp	t Status (as defined by M.G.	L. c. 21E, s. 2)
3. Agency or Public U	Utility on a Right of Way (as defined	by M.G.L. c. 21E, s. 5(j))	
4. Any Other Person	Undertaking Response Actions:	Specify Relationship:	
H. REQUIRED ATTAC	CHMENT AND SUBMITTALS:		
	n of the IRA Completion Statement.		ored, treated, managed, recycled or reused at the site must submit one of the following plans, along with
a. A Release Ab	atement Measure (RAM) Plan (BWS	SC106)	IV Remedy Implementation Plan (BWSC108)
			were) subject to any order(s), permit(s) and/or statement identifying the applicable provisions
	ify that the Chief Municipal Officer a Action taken to control, prevent, ab		th were notified of the implementation of an nt Hazard.
	ify that the Chief Municipal Officer and the Response Action taken to co		th were notified of the submittal of a Completion inate an Imminent Hazard.
5. Check here if any to BWSC.eDEP@sta		I on this form is incorrect, e	e.g. Release Address/Location Aid. Send corrections

Revised: 11/14/2013 Page 5 of 6

№ 6. Check here to certify that the LSP Opinion containing the material facts, data, and other information is attached.



Immediate Response Action (IRA) Transmittal FormPursuant to 310 CMR 40.0424 - 40.0427 (Subpart D)

BWSC 105

Release Tracking Number

	_		
4	-	26179	

I. CERTIFICATION OF PERSON UNDERTAKING IR

that, b contai knowl CMR 4 310 C respon signifi	, attest under the miliar with the information contained in this submittal, included on my inquiry of the/those individual(s) immediate and herein is, to the best of my knowledge, information ledge, information and belief, I/the person(s) or entity(ies) 40.0183(2); (iv) that I/the person(s) or entity(ies) on whose MR 40.0183(5); and (v) that I am fully authorized to maisble for this submittal. I/the person(s) or entity(ies) of icant penalties, including, but not limited to, possible finitely plete information.	luding any and all ly responsible for and belief, true, ac on whose behalf t behalf this submitt ake this attestatio on whose behalf th	obtaining the information, the material information ccurate and complete; (iii) that, to the best of my his submittal is made satisfy(ies) the criteria in 310 ral is made have provided notice in accordance with n on behalf of the person(s) or entity(ies) legally his submittal is made is/are aware that there are
2. By:		3. Title:	
4. For:	BARNSTABLE COUNTY COMMISSIONERS	5. Date:	(mm/dd/yyyy)
6. Chec	k here if the address of the person providing certification is	s different from add	dress recorded in Section F.
7. Street:			
8. City/Town	n:	9. State:	10. Zip Code:
11. Telephor	ne:12. Ext:	13. Email:	
	YOU ARE SUBJECT TO AN ANNUAL COMPLIANCE YEAR FOR THIS DISPOSAL SITE. YOU MUST LEGIB FORM OR DEP MAY RETURN THE DOCUMENT AS FORM, YOU MAY BE PENALIZED FO	LY COMPLETE AI S INCOMPLETE. IF	L RELEVANT SECTIONS OF THIS YOU SUBMIT AN INCOMPLETE

Date Stamp (DEP USE ONLY:)

Revised: 11/14/2013 Page 6 of 6



Massachusetts Department of Environmental Protection Bureau of Waste Site Cleanup IRA REMEDIAL MONITORING REPORT Pursuant to 310 CMR 40.0400 (SUBPART D)

Remedial System or Monitoring Program: 1

of: 1

Release Tracking Number

BWSC105-A

26179

A. DESCRIPTION OF ACTIVE OPERATION AND MAINTENANCE ACTIVITY:	
1. Type of Active Operation and Maintenance Activity: (check all that apply)	
✓ a. Active Remedial System: (check all that apply)	
☐ i. NAPL Recovery ☐ ii. Soil Vapor Extraction/Bioventing ☐ iii. Vapor-ph	ase Carbon Adsorption
•	phase Carbon Adsorption
□ vii. Air Stripping □ viii. Sparging/Biosparging □ ix. Cat/Then	•
\Box x. Other Describe:	
☐ b. Active Exposure Pathway Elimination Measure	ii. Drinking Water
	II. Drinking water
c. Application of Remedial Additives: (check all that apply)	
☐ i. To the Subsurface ☐ ii. To Groundwater (Injection) ☐ iii. To the Su	
d. Active Remedial Monitoring Program Without the Application of Remedial Additives: (check	
and E are not required; attach supporting information, data, maps and/or sketches needed by check	ing Section G5)
☐ i. Reactive Wall ☐ ii. Natural Attenuation ☐ iii. Other ☐ Describe:	
2. Mode of Operation: (check one)	
■ a. Continuous □ b. Intermittent □ c. Pulsed □ d. One-time Event Only □ e. Othe	r:
3. System Effluent/Discharge: (check all that apply)	
a. Sanitary Sewer/POTW	
■ b. Groundwater Re-infiltration/Re-injection: (check one) □ i. Downgradient □ ii. Upgrad	ient
	Off-gas Controls
d. Drinking Water Supply	C
e. Surface Water (including Storm Drains)	
f. Other Describe:	
B. MONITORING FREQUENCY:	
	0/2020
(mm/dd/yyyy)	(mm/dd/yyyy)
2. Number of monitoring events during the reporting period: (check one)	
a. System Startup: (if applicable)	
i. Days 1, 3, 6, and then weekly thereafter, for the first month.	
ii. Other Describe:	
▶ b. Post-system Startup (after first month) or Monitoring Program:	
▼ i. Monthly	
☐ ii. Quarterly	
☐ iii. Annually	
iv. Other Describe:	
3. Check here to certify that the number of required monitoring events were conducted during the	reporting period.
C. EFFLUENT/DISCHARGE REGULATION: (check one to indicate how the effluent/discharge lim	its were established)
☐ 1. NPDES: (check one) ☐ a. Remediation General Permit ☐ b. Individual Permit	,
c. Emergency Exclusion Effective Date of Permit:	
<i>y</i>	(mm/dd/yyyy)
☐ 2. MCP Performance Standard MCP Citations(s):	(IIIII) dd/yyyy)
T 2 DED A managed Letters Date of Letters 4449 19949	
▼ 3. DEP Approval Letter Date of Letter: 11/18/2016	
3. DEP Approval Letter Date of Letter. 11/18/2016 (mm/dd/yyyy)	



Massachusetts Department of Environmental Protection

Bureau of Waste Site Cleanup

IRA REMEDIAL MONITORING REPORT

Pursuant to 310 CMR 40.0400 (SUBPART D)

Remedial System or Monitoring Program: 1	
--	--

	1
of:	1

В	W	S	CI	0	5	-A

Release Tracking Number
4 - 26179

 Required due to Rer a. Name: TJMCGOFF 	irodiai (, asto.			b. Grad	le: 4		
c. License No: 15570		d Licens	e Exp. Da	te: 12/31/2021			
- Electise 140. 15570			с Елр. Би	(mm/dd/yyyy)			
2. Not Required				(111111/44/3333)			
3. Not Applicable							
* *	EMEDIAL SY	YSTEM OR A	CTIVE R	REMEDIAL MONITORIN	NG PROGRA	M DURING	
PORTING PERIOD: (ch			CIIVEI		(GTROGIC	an Delai (G	
*	-		e or more	days during the Reporting	g Period.		
a. Days System was F	ully Function	al: 30		b. GW Recover	red (gals): 4	58937	
c. NAPL Recovered (g	gals):	-		d. GW Dischar	ged (gals):	458937	
e. Avg. Soil Gas Reco	very Rate (sc	fm):		f. Avg. Spargin	g Rate (scfm):	
2. Remedial Additives:	(check all tha	t apply)			•	·	
	nediation Add	tives applied:	(total qua	ntity applied at the site for ii. Peroxides:	the current re	eporting period	d)
	nediation Add	tives applied:	(total qua		the current re	eporting period	d)
☐ b. Enhanced Biorem	nediation Add	Quantity	(total quan		Date	Quantity	d) Units
☐ b. Enhanced Biorem ☐ i. Nitrogen/Phospl	nediation Addi		` •	ii. Peroxides:			
☐ b. Enhanced Biorem ☐ i. Nitrogen/Phospl	nediation Addi		` •	ii. Peroxides:			
□ b. Enhanced Biorem □ i. Nitrogen/Phospl Name of Additive	horus: Date		` •	ii. Peroxides:			
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive	nediation Addinorus: Date Date	Quantity	Units	Name of Additive	Date	Quantity	Units
□ b. Enhanced Biorem □ i. Nitrogen/Phospl Name of Additive	horus: Date		` •	Name of Additive			
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive	nediation Addinorus: Date Date	Quantity	Units	Name of Additive	Date	Quantity	Units
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive	nediation Addinorus: Date Date	Quantity	Units	Name of Additive	Date	Quantity	Units
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive iii. Microorganism Name of Additive	Date Date Date	Quantity Quantity	Units Units	Name of Additive iv. Other: Name of Additive	Date	Quantity Quantity	Units
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive iii. Microorganism Name of Additive	Date Date Date	Quantity Quantity	Units Units	Name of Additive	Date	Quantity Quantity	Units
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive iii. Microorganism Name of Additive c. Chemical oxidation i. Permanganates:	Date Date Date	Quantity Quantity dditives appli	Units Units Units	Name of Additive iv. Other: Name of Additive iv. Other: Name of Additive quantity applied at the site ii. Peroxides:	Date	Quantity Quantity Quantity nt reporting pe	Units Units riod)
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive iii. Microorganism Name of Additive	Date Date Date Date Don/reduction a	Quantity Quantity	Units Units	Name of Additive iv. Other: Name of Additive	Date Date for the curren	Quantity Quantity	Units
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive iii. Microorganism Name of Additive c. Chemical oxidation i. Permanganates:	Date Date Date Date Don/reduction a	Quantity Quantity dditives appli	Units Units Units	Name of Additive iv. Other: Name of Additive iv. Other: Name of Additive quantity applied at the site ii. Peroxides:	Date Date for the curren	Quantity Quantity Quantity nt reporting pe	Units Units riod)
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive iii. Microorganism Name of Additive c. Chemical oxidation i. Permanganates: Name of Additive	Date Date Date Date Don/reduction a	Quantity Quantity dditives appli	Units Units Units	Name of Additive iv. Other: Name of Additive quantity applied at the site ii. Peroxides: Name of Additive	Date Date for the curren	Quantity Quantity Quantity nt reporting pe	Units Units riod)
b. Enhanced Biorem i. Nitrogen/Phospl Name of Additive iii. Microorganism Name of Additive c. Chemical oxidation i. Permanganates:	Date Date Date Date Don/reduction a	Quantity Quantity dditives appli	Units Units Units	Name of Additive iv. Other: Name of Additive iv. Other: Name of Additive quantity applied at the site ii. Peroxides:	Date Date for the curren	Quantity Quantity Quantity nt reporting pe	Units Units riod)

Revised: 11/13/2013 Page 2 of 3



Massachusetts Department of Environmental Protection Bureau of Waste Site Cleanup IRA REMEDIAL MONITORING REPORT

Pursuant to 310 CMR 40.0400 (SUBPART D)

Remedial System or Monitoring Program: 1	
--	--

of:	1

B	WS	C1	05	-A

Release Tracking Number

4	-	26179
---	---	-------

E. STATUS OF ACTIVE REMEDIAL SYSTEM OR ACTIVE REMEDIAL MONITORING PROGRAM DURING **REPORTING PERIOD: (cont.)**

- 11	Y C 4 1 11::	ъ.	0	TT	1 27 011111		0	TT
F	Name of Additive	Date	Quantity	Units	Name of Additive	Date	Quantity	Units
	e. Check here if any Additive, Date Applied				e applied. Attach list of add s. or lbs.)	litional additi	ves and includ	e Name o
		E REMEDIA	AL SYSTEM	OR ACT	TVE REMEDIAL MONI	TORING PR	OGRAM: (ch	eck all th
ipply)		System had a	unscheduled	shutdown	s on one or more occasion	s during the	Reporting Per	iod
,						_		iou.
	a. Number of Unschedu		-	D. 1	otal Number of Days of U	nscheduled S	snutdowns:	
	c. Reason(s) for Unsche	duled Shutd	owns:					
~	2. The Active Remedial	System had	scheduled sh	utdowns o	on one or more occasions	luring the Re	porting Period	l.
	a. Number of Scheduled	Shutdowns	: 1	b. T	otal Number of Days of S	cheduled Shu	ıtdowns: 0.	2
	c. Reason(s) for Schedu	led Shutdow	ns: VACUL	IM REMOVA	L OF IRON OXIDE SEDIMENT IN	EQ TANK	_	
	3. The Active Remedial S	System or A	tive Remedi	al Monito	ring Drogram was narman	ently shutdow	m/discontinuo	1 1
Rei	norting Period			ai wioiito	ring Frogram was perman	siitiy siiutdow	/II/discontinue	a auring
Re	porting Period. a. Date of Final System	or Monitorir				antry shutdow	/II/discontinue	a auring
Rej	. •	or Monitorir					/ii/discontinue	a auring
	. •		ng Program S			—	n/discontinue	a during
	a. Date of Final System b. No Further Effluen	t Discharges	ng Program S	hutdown:		_		
	a. Date of Final System □ b. No Further Effluen □ c. No Further Applica	t Discharges	ng Program S	hutdown:	(mm/dd/yyyy)	_		
	a. Date of Final System b. No Further Effluen c. No Further Applica 310 CMR 40.0046.	t Discharges tion of Reme tals Planned.	ng Program S	hutdown:	(mm/dd/yyyy)	_		
G. SU	a. Date of Final System b. No Further Effluen c. No Further Applica 310 CMR 40.0046. d. No Further Submitt e. Other: Describe	t Discharges tion of Reme tals Planned. :	ng Program S dial Additive	es planned	(mm/dd/yyyy)	mpleted to de	monstrate com	npliance v
G. SU 1 1 1 1 1 1 1 1.	a. Date of Final System b. No Further Effluen c. No Further Applica 310 CMR 40.0046. d. No Further Submitt e. Other: Describe MMARY STATEMENT All Active Remedial Sysable. There were no significan	t Discharges tion of Reme tals Planned. : S: (check all tem checks a	ng Program S dial Additive that apply fo	es planned or the curr	(mm/dd/yyyy) ; sufficient monitoring content reporting period)	mpleted to de	monstrate com	opliance v
G. SU 1	a. Date of Final System b. No Further Effluen c. No Further Applica 310 CMR 40.0046. d. No Further Submitt e. Other: Describe MMARY STATEMENTS All Active Remedial Sysable. There were no significan m.	t Discharges tion of Reme tals Planned. S: (check all tem checks a t problems of	that apply found effluent a	es planned or the currinalyses re	(mm/dd/yyyy) c; sufficient monitoring content reporting period) equired by the approved pl	an and/or per	mit were performs of the Activ	ormed where the Remedule

5. Check here if additional/supporting Information, data, maps, and/or sketches are attached to the form.

Revised: 1/13/2013 Page 3 of 3



Massachusetts Department of Environmental Protection Bureau of Waste Site Cleanup IRA REMEDIAL MONITORING REPORT

MEASUREMENTS

Pursuant to 310 CMR 40.0400 (SUBPART D) Remedial System or Monitoring Program:

of:

Release Tracking Number

BWSC105-B

26179 4

For each Point of Measurement, related to concentration indicate the highest concentration detected during the reporting period, of each oil, hazardous material and/or remedial additive.

For each Point of Measurement for pressure differentials, indicate the lowest pressure differential detected during the reporting period.

Point of Measurement	Date (mm/dd/yyyy)	Contaminant, Measurement and/or Indicator Parameter	Influent Concentration (where applicable)		(check one) Discharge GroundWater Concentration Pressure Differential	Check here, if ND/BDL	Permissible Concentration or Pressure Differential	Units	Within Permissible Limits? (Y/N)
SYSTEM	04/28/2020	PFAS	2.302	0.105		✓	0.020	UG/L	YES

Check here if any additional BWSC105 B, Measurements Form(s), are needed.

Revised: 11/17/2013 Page 1 of 1



Massachusetts Department of Environmental Protection Bureau of Waste Site Cleanup IRA REMEDIAL MONITORING REPORT

Pursuant to 310 CMR 40.0400 (SUBPART D)

Remedial System or Monitoring Program:

2	of:	2

BWSC105-A

Release Tracking Number

			\mathcal{C}	
4	-	261	79	

A. DESCRIPTION OF ACTIVE OPE 1. Type of Active Operation and Maint			
a. Active Remedial System: (chec	k all that apply)	_	
 □ i. NAPL Recovery ☑ iv. Groundwater Recovery □ vii. Air Stripping □ x. Other Describe: 	☐ ii. Soil Vapor Extraction/Bio☐ v. Dual/Multi-phase Extract☐ viii. Sparging/Biosparging	ion	or-phase Carbon Adsorption leous-phase Carbon Adsorption Thermal Oxidation
☐ b. Active Exposure Pathway Elim	ination Measure igation System to address (check	one):	☐ ii. Drinking Water
☐ c. Application of Remedial Addition i. To the Subsurface ☐ d. Active Remedial Monitoring Pand E are not required; attach support i. Reactive Wall ☐ ii. Nat	ii. To Groundwater (Injection of the Application of	Remedial Additives: (cl	
2. Mode of Operation: (check one) ✓ a. Continuous – b. Intermi		time Event Only	Other:
 System Effluent/Discharge: (check a ☐ a. Sanitary Sewer/POTW 	ll that apply)		
 □ b. Groundwater Re-infiltration/Re □ c. Vapor-phase Discharge to Aml □ d. Drinking Water Supply 		•	ogradient No Off-gas Controls
☐ e. Surface Water (including Storn	n Drains)		
f. Other Describe:			
B. MONITORING FREQUENCY: 1. Reporting period that is the subject of	of this submittal: From: 4	/1/2020 To:	4/30/2020 (mm/dd/yyyy)
2. Number of monitoring events during ☐ a. System Startup: (if applicable) ☐ i. Days 1, 3, 6, and then week ☐ ii. Other Describe:		, , , , , , , , , , , , , , , , , , , ,	(11111111111111111111111111111111111111
 ▶ b. Post-system Startup (after firs ▶ i. Monthly □ ii. Quarterly □ iii. Annually □ iv. Other Describe: 	t month) or Monitoring Program:		
□ 3. Check here to certify that the nur	nber of required monitoring even	ts were conducted durin	g the reporting period.
C. EFFLUENT/DISCHARGE REGUL ☐ 1. NPDES: (check one) ☐ a.			e limits were established) mit
			(mm/dd/yyyy)
☐ 2. MCP Performance Standard	MCP Citations(s):		
▼ 3. DEP Approval Letter Date of	Letter: 11/18/2016 (mm/dd/yyyy)		
4. Other Describe:			



Massachusetts Department of Environmental Protection

Bureau of Waste Site Cleanup

IRA REMEDIAL MONITORING REPORT

Pursuant to 310 CMR 40.0400 (SUBPART D)

Remedial System or Monitoring Program: 2

	<i>D</i>	
2		

of: 2

BWSC105 -A

Release Tracking Number

4	-	26179	

a. Name: TJMCGOFF				b. Grad	le: 4		
c. License No: 15570		d. Licens	se Exp. Da	te: 12/31/2021			
				(mm/dd/yyyy)			
2. Not Required							
3. Not Applicable							
			ACTIVE R	EMEDIAL MONITORIN	NG PROGRA	M DURING	
ORTING PERIOD: (chec		1 0 /		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	D : 1		
	•		ne or more	days during the Reporting			
a. Days System was Full	•	ıl: <u>30</u>		b. GW Recover		50745	
c. NAPL Recovered (gal				d. GW Dischar	/	550745	
e. Avg. Soil Gas Recove	•			f. Avg. Spargin	g Rate (scfm):	
2. Remedial Additives: (c	check all that	t apply)					
		during the Re	porumgre				
		-		ntity applied at the site for ii. Peroxides:	the current re	eporting period	1)
☐ b. Enhanced Bioremed		-		ntity applied at the site for	the current re	Quantity	Units
□ b. Enhanced Bioremed □ i. Nitrogen/Phospho	rus:	tives applied:	(total qua	ntity applied at the site for ii. Peroxides:			
☐ b. Enhanced Bioremed ☐ i. Nitrogen/Phospho	rus:	tives applied:	(total qua	ntity applied at the site for ii. Peroxides:			
□ b. Enhanced Bioremed □ i. Nitrogen/Phospho Name of Additive	rus: Date	tives applied:	(total qua	ntity applied at the site for ii. Peroxides: Name of Additive			
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive	rus: Date	Quantity	Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other:	Date	Quantity	Units
□ b. Enhanced Bioremed □ i. Nitrogen/Phospho Name of Additive	rus: Date	tives applied:	(total qua	ntity applied at the site for ii. Peroxides: Name of Additive			
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive	rus: Date	Quantity	Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other:	Date	Quantity	Units
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive	rus: Date	Quantity	Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other:	Date	Quantity	Units
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive iii. Microorganisms: Name of Additive	Date Date	Quantity Quantity Quantity	Units Units Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other: Name of Additive	Date	Quantity Quantity	Units
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive iii. Microorganisms: Name of Additive	Date Date	Quantity Quantity Quantity	Units Units Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other:	Date	Quantity Quantity	Units
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive iii. Microorganisms: Name of Additive	Date Date	Quantity Quantity Quantity	Units Units Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other: Name of Additive	Date	Quantity Quantity	Units
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive iii. Microorganisms: Name of Additive c. Chemical oxidation i. Permanganates:	Date Date Date /reduction as	Quantity Quantity Quantity dditives appli	Units Units Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other: Name of Additive quantity applied at the site ii. Peroxides:	Date Date for the curren	Quantity Quantity nt reporting pe	Units Units Units
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive iii. Microorganisms: Name of Additive c. Chemical oxidation i. Permanganates:	Date Date Date /reduction as	Quantity Quantity Quantity dditives appli	Units Units Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other: Name of Additive quantity applied at the site ii. Peroxides:	Date Date for the curren	Quantity Quantity nt reporting pe	Units Units Units
b. Enhanced Bioremed i. Nitrogen/Phospho Name of Additive iii. Microorganisms: Name of Additive c. Chemical oxidation i. Permanganates:	Date Date Date /reduction as	Quantity Quantity Quantity dditives appli	Units Units Units	ntity applied at the site for ii. Peroxides: Name of Additive iv. Other: Name of Additive quantity applied at the site ii. Peroxides:	Date Date for the curren	Quantity Quantity nt reporting pe	Units Units Units



IRA REMEDIAL MONITORING REPORT

Pursuant to 310 CMR 40.0400 (SUBPART D)

Remedial System or Monitoring Program:

	_	
2	of:	2

BWSC105 - A

Release Tracking Number

4	-	26179	

E. STATUS OF ACTIVE REMEDIAL SYSTEM OF	R ACTIVE REMEDIAL MONITORING PROGRAM DURING
REPORTING PERIOD: (cont.)	

d. Other additives applied: (total quantity applied at the site for the current reporting period) Name of Additive Date **Ouantity** Units Name of Additive Quantity Units Date e. Check here if any additional Remedial Additives were applied. Attach list of additional additives and include Name of Additive, Date Applied, Quantity Applied and Units (in gals. or lbs.) F. SHUTDOWNS OF ACTIVE REMEDIAL SYSTEM OR ACTIVE REMEDIAL MONITORING PROGRAM: (check all that apply) 1. The Active Remedial System had unscheduled shutdowns on one or more occasions during the Reporting Period. a. Number of Unscheduled Shutdowns:

b. Total Number of Days of Unscheduled Shutdowns: c. Reason(s) for Unscheduled Shutdowns: ▼ 2. The Active Remedial System had scheduled shutdowns on one or more occasions during the Reporting Period. b. Total Number of Days of Scheduled Shutdowns: a. Number of Scheduled Shutdowns: c. Reason(s) for Scheduled Shutdowns: VACUUM REMOVAL OF ACCUMULATED IRON-OXIDE SEDIMENTS IN EQ TANK 3. The Active Remedial System or Active Remedial Monitoring Program was permanently shutdown/discontinued during the Reporting Period. a. Date of Final System or Monitoring Program Shutdown: (mm/dd/yyyy) □ b. No Further Effluent Discharges. C. No Further Application of Remedial Additives planned; sufficient monitoring completed to demonstrate compliance with 310 CMR 40.0046. d. No Further Submittals Planned. e. Other: Describe: **G. SUMMARY STATEMENTS:** (check all that apply for the current reporting period) ▼ 1. All Active Remedial System checks and effluent analyses required by the approved plan and/or permit were performed when applicable. ▼ 2. There were no significant problems or prolonged (>25% of reporting period) unscheduled shutdowns of the Active Remedial System. ▼ 3. The Active Remedial System or Active Remedial Monitoring Program operated in conformance with the MCP, and all applicable approval conditions and/or permits. 4. Indicate any Operational Problems or Notes:

Revised: 1/13/2013 Page 3 of 3

5. Check here if additional/supporting Information, data, maps, and/or sketches are attached to the form.



Massachusetts Department of Environmental Protection Bureau of Waste Site Cleanup IRA REMEDIAL MONITORING REPORT

MEASUREMENTS
Pursuant to 310 CMR 40.0400 (SUBPART D)
Remedial System or Monitoring Program:

of: 2

Release Tracking Number

BWSC105-B

4 26179

For each Point of Measurement, related to concentration indicate the highest concentration detected during the reporting period, of each oil, hazardous material and/or remedial additive.

For each Point of Measurement for pressure differentials, indicate the lowest pressure differential detected during the reporting period.

Point of Measurement	Date (mm/dd/yyyy)	Contaminant, Measurement and/or Indicator Parameter	Influent Concentration (where applicable)		(check one) Discharge GroundWater Concentration Pressure Differential	Check here, if ND/BDL	Permissible Concentration or Pressure Differential	Units	Within Permissible Limits? (Y/N)
SYSTEM	04/28/2020	PFAS	2.302	0.081	0.001		0.020	UG/L	YES

Check here if any additional BWSC105 B, Measurements Form(s), are needed.

Revised: 11/17/2013 Page 1 of 1

SAMPLE ID USEPA Method 537.2	DEOC /e - /l'	DEOA /r-//\		T (PRW-4)	DELIMA / // \	DED A /n - /13	DEOC (n - /1)	DEO 4 /2 - /1 \		POINT	DEU / // `	DED 4 /n - /13	DEOC /w - // \	DECA //13		UENT	DELIMA (~ - ft.)	DEDA / // \
MassDEP ORS Guidline ²	PFOS (ng/L)	PFOA (ng/L)		ng/L	PFHPA (ng/L)	PFDA (ng/L)	PFUS (ng/L)	PFOA (ng/L)	70 i		PFHPA (ng/L)	PFDA (ng/L)	PFOS (ng/L)	PFOA (ng/L)		ng/L	PFHPA (ng/L)	PFDA (ng/L)
MCP Method 1 GW-1																		
Standard ³			20	ng/L					20 ו	ng/L					20	ng/L		
SAMPLE DATE		,	,					,					_	,				
4/1/2015	760	60	A	A	^ A	A A			A	A	A	^ A			^A	A	^A	A
7/17/2015 8/4/2015	5600 5900	460 550	A	A	A	'A			A	A	A	A			A	^A	A	A
9/30/2015	17000	840	A	A	A	A			A	A	A	A			A	A	A	A
10/15/2015	9900	560	^A	^A	A	^A	BRL (<9.4)	BRL (<5.3)	A	A	A	A	9.4	BRL (<5.8)	A	A	A	A
11/12/2015	9000	BRL (<2000)	A	A	A	A	BRL (<3.3)		A	A	^A	^A			^A	A	A	A
1/6/2016 1/21/2016	7600 5200	260 160	^^	^	A	^ A	120 270	75 16	^ A	A	^	^			A	A	^	A
2/3/2016	3500	140	A	A	A	A	540	26	A	A	A	A			A	A	A	A
2/17/2016	4500	140	A	A	A	A	520	24	A	A	^A	A			^A	A	A	A
3/8/2016	3700	140	A	A	A	A	420	19	A	A	A	A	BRL (<3.3)	BRL (<5.3)	A	A	A	A
3/23/2016	5000	150	A A	A A	A A	A A	650	39	A A	A A	A	^ ^	BRL (<3.3)	BRL (<5.3)	A	A	A A	^ A
4/14/2016 4/28/2016	4800 6300	140 BRL (<200)	 A	 A	 A	 A	610	26	 A	A	 A	 A	BRL (<3.3) BRL (<20)	BRL (<5.3) BRL (<20)	 A	 A	 A	 A
5/12/2016	6800	BRL (<200)	A	A	A	A			A	A	A	A	BRL (<20)	BRL (<20)	A	A	A	A
5/25/2016	6900	BRL (<210)	^A	^A	A	^A			A	A	A	A	BRL (<3.3)	BRL (<5.3)	A	A	A	A
6/16/2016	7800	160	A	A	A	A			A	A	^A	^A	BRL (<3.3)	BRL (<5.3)	^A	A	A	^A
7/6/2016	7600	270	^ A	^A	A	^ A	1600	 54	^ A	^ A	_A A	A	10	BRL (<5.3)	^ A	^ A	^ A	^ A
8/11/2016	13000	160						ge conducted aft					BRL (<3.3)	BRL (<5.3)				
8/18/2016	9500	210	A	A	A	A	BRL (<3.3)	BRL (<5.3)	A	A	A	A	BRL (<3.3)	BRL (<5.3)	A	A	A	_A
9/8/2016	9500	190	A	A	A	A	8.5	5.3	A	A	_A	A	BRL (<3.3)	BRL (<5.3)	A	A	A	A
10/6/2016	17000	250	A A	A A	A A	A A	110	8.3	A A	A A	A A	A A	BRL (<3.3)	BRL (<5.3)	A A	A	A	A
10/20/2016 11/3/2016	7200 7900	130 110	^	^	^ A	^ A	1000 650	BRL (<5.3) BRL (<5.3)	^ A	^	^ A	^ A	BRL (<3.3) BRL (<3.3)	BRL (<5.3) BRL (<5.3)	^ A	^ A	^ A	^ A
11/17/2016	5400	99	A	A	A	 A	1200	NA NA	A	A	 A	 A	17	NA NA	A	A	 A	 A
12/1/2016	5300	100	_A	_A	A	_A	400	14	A	A	A	A			A	A	A	A
12/14/2016	5700	95	A	A	A	A	82	BRL (<5.3)	A	A	A	A	8.1	BRL (<5.3)	A	A	A	A
1/4/2017 2/16/2017	4900 2800	95 88	A A	A	A	^ A	360 1000	15 39	^ A	^ A	A A	A A	BRL (<3.3) 25	BRL (<5.3) BRL (<5.3)	A	A	^ A	A
3/1/2017	3700	120	A	A	A	A	1400	47	A	A	A	A	150	6.5	A	A	A	A
3/23/2017	3800	87	A	A	^A	A	2000	71	A	A	A	A	160	9.5	A	A	A	A
5/3/2017	2400	86	A	A	A	A			A	A	A	A	BRL (<2.6)	BRL (<4.6)	A	A	A	A
4/10/2017	2200	110	A	A	A	_A		arbon change co	nducted on 04/	3/17.	A	A	PDI (2 ()	DDI / 4 /)	A	A	_A	A
4/19/2017 5/18/2017	3200 3000	110 110	 A	 A	 A	 A	160 570	BRL (<4.6) 32	A	A	 A	 A	BRL (<2.6) BRL (<2.6)	BRL (<4.6) BRL (<4.6)	 A	 A	 A	 A
6/1/2017	3200	110	_ A	A	A	A	730	33	_A	A	_ A	A	4.1	BRL (<4.6)	_ A	A	A	_ A
6/27/2017	2600	99	A	A	_A	A			_A	A	A	_A	210	15	A	A	A	A
7/18/2017	3500	97	A	^A	A	^A	2300	72	A	^A	A	^A	49	25	^A	^A	A	A
8/16/2017	3000	110	A	A	A	A	BRL (<2.3)	Carbon change c BRL (<4.1)	onducted on 8/0	A	A	A	BRL (<2.3)	BRL (<4.1)	A	A	A	A
8/28/2017	2900	100	^A	A	A	A	27	BRL (<20)	A	A	A	A			A	A	A	A
10/2/2017	3200	85	A	A	_A	A	510	25	_A	A	A	A	BRL (<2.6)	BRL (<4.6)	A	A	A	A
10/12/2017	4500	110	A A	A A	^ ^	A A	960	29	A A	A A	A A	A A	BRL (<2.6)	BRL (<4.6)	A	A	A	A
11/9/2017 11/20/2017	2400 2000	77 64	A	'A	A	A	520	 15	A	A	A	A	BRL (<6.0) BRL (<6.0)	BRL (<3.3) BRL (<3.3)	^	A	A	A
12/7/2017	1600	64	A	A	A	A	780	34	A	A	A	A	11	BRL (<3.3)	A	A	A	A
2/5/2018	2100	27	A	A	A	^A	390	13	A	A	A	A	BRL (<6.0)	BRL (<3.3)	^A	^A	A	A
2/14/2018	2100	30	^A	^A	A	^A	850	27	A	^A	A	A	11	BRL (<3.3)	^A	^A	^A	A
4/9/2018	2,600	79	_A	A	A	System ^A	shutdown on 2/ 990	14/18 due to tra 25	nsfer pump failu ^A	re; system resta	rt on 4/9/18.	A	BRL (<20)	BRL (<20)	A	A	A	A
4/13/2018	3100	62	A	A	A	A	1500	35	A	A	A	A	30 30	BRL (<20)	A	A	A	A
5/9/2018	1800	73	A	A	A	A	490	26	_A	A	A	A	BRL (<6.0)	BRL (<33)	A	A	A	A
					Syst	em shutdown on						alarm fail.						
6/14/2018	2800	120	79	540	110	A (Carbon change c 200	onducted on 06/ 9.4	05/18; system re BRL (<8.7)	estarted on 06/0 38	07/18. 11	A	BRL (<6.0)	BRL (<3.3)	BRL (<8.7)	BRL (<5.6)	BRL (<7.4)	A
7/13/2018	2400	100	73	600	90	A	1100	44	27	24	35	A	BRL (<0.0)	BRL (<3.3)	BRL (<0.7)	BRL (<5.6)	BRL (<7.4)	A
8/7/2018	2900	95	73	460	86	A	630	31	22	130	34	A	27	5.3	BRL (<8.7)	9.1	BRL (<7.4)	A
9/27/2018	4300	69	50	360	190	A	3600	69	49	330	65	^A	81	BRL (<3.3)	BRL (<8.7)	14	BRL (<7.4)	^A
10/30/2018	2800	65	46	320	71	A	Carbon change c	onducted on 09/	28/18; system re 8.7	estarted on 10/0	78	A	BRL (<6.0)	BRL (<3.3)	BRL (<8.7)	BRL (<5.6)	BRL (<7.4)	A
11/16/2018	2900	62	50	290	77	A	460	24	19	94	26	A	BRL (<6.0)	BRL (<3.3)	BRL (<8.7)	BRL (<5.6)	BRL (<7.4)	A
12/14/2018	1900	62	49	300	70	_A	1200	40	30	180	45	A	BRL (<6.0)	BRL (<3.3)	BRL (<8.7)	BRL (<5.6)	BRL (<7.4)	A
1/10/2019	2400	84	68	410	96	A	2200	71	54	360	82	A	21	BRL (<3.3)	BRL (<8.7)	BRL (<5.6)	BRL (<7.4)	A
2/15/2010	4400	120	120	FFA	110	A		e conducted on 2				A	DDI / ./ o\	DDI / .0.0\	DDI / .0 3\	DDI / ./ 3\	ppi /.¬ A\	A
2/15/2019 3/11/2019	4600 5600	130 120	120 120	550 520	110 98	 A	560 63	14 BRL(<3.3)	14 BRL (<4.9)	62 BRL (<5.6)	14 BRL (<7.1)		BRL (<6.0) BRL (<6.0)	BRL (<3.3) BRL (<3.3)	BRL (<8.7) BRL (<4.9)	BRL (<6.2) BRL (<5.6)	BRL (<7.4) BRL (<7.1)	A
57.172017						n sediments pum		. ,	. ,	. ,				(.0.0)	(-7-7)	(.0.0)	(-7-1)	·
4/9/2019	6600	140	180	580	99	A	400	7.4	9.9	31	BRL (<7.1)	^A	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	^A
5/21/2019	2500	83	59	290	100	8.6	3400	72	69	260	7.8	12	BRL (<12)	BRL (<7.4)	BRL(<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
6/27/2019	8400	86	120	340	68	26	Carbon change c BRL (<5.2)	onducted on 06/ BRL (<7.4)	13/19; system re BRL (<4.9)	estarted on 06/1 BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
7/29/2019	9500	78	100	290	72	16	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
8/22/2019	8300	64	100	260	63	20	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
9/26/2019	4900	65	82	220	64	21	64	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
10/30/2019 11/12/2019	3800 4200	63 53	85 85	230 200	72 59	19 15	51 120	BRL (<7.4) BRL (<7.4)	BRL (<4.9) BRL (<4.9)	5.9 BRL (<5.2)	BRL (<7.1) BRL (<7.1)	BRL (<4.1) BRL (<4.1)	BRL (<5.2) BRL (<5.2)	BRL (<7.4) BRL (<7.4)	BRL (<4.9) BRL (<4.9)	BRL (<5.2) BRL (<5.2)	BRL (<7.1) BRL (<7.1)	BRL (<4.1) BRL (<4.1)
12/17/2019	1500	43	51	180	59	10	530	16	17	63 63	22	4.5	BRL (<5.2)	BRL (<7.4)	BRL (<4.9) BRL (<4.9)	BRL (<5.2) BRL (<5.2)	BRL (<7.1)	BRL (<4.1) BRL (<4.1)
								onducted on 12/					(.0.2)	(-77)	(/)	((-1-1)	
1/17/2020	2200	57	60	220	69	13	11	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
2/13/2020 3/3/2020	3100 3300	74 72	66 64	310 300	92 81	17 14	BRL (<5.2) 7.4	BRL (<7.4) BRL (<0.23)	BRL (<4.9) BRL (<0.48)	BRL (<5.2) BRL (<0.33)	BRL (<7.1) BRL (<0.37)	BRL (<4.1) BRL (<0.18)	BRL (<5.2) 0.60	BRL (<7.4) BRL (<0.23)	BRL (<4.9) BRL (<0.48)	BRL (<5.2) BRL (<0.33)	BRL (<7.1) BRL (<0.37)	BRL (<4.1) BRL (<0.18)
JI JI ZUZU					56	42	86	2.7	2.2	10	3.4	0.51	BRL (<0.43)	BRL (<0.23)	BRL (<0.48)	BRL (<0.33)		BRL (<0.18)
4/28/2020	1900	52	42	210	56	42	00	2.1								DKF (<0.33)	BRL (<0.37)	DKL (<0.10)

- Notes:

 1. Concentrations presented in ng/L nanograms per Liter parts per trillion

 2. * Prior to June 11, 2018, the USEPA established the EPA Health Advisory for two PFAS chemicals, PFOA, and PFOS, which was 70 ng/L. Subsequently, MassDEP's Office of Research and Standards (ORS) expanded on this Health Advisory and created the ORS Guideline that applied to the total summed of five PFAS chemicals, PFOS, PFOA, PFNA, PFHxS, and PFHpA, effective June 11, 2018.

 3. On December 13, 2019, MassDEP published the newly established clean up standards for PFAS in soil and groundwater. These standards were effective as of December 27, 2019 and apply to the total sum of six PFAS chemicals, PFOS, PFOA, PFNA, PFHxS, pFHpA, and PFDA; the new standard is 20 ng/L or parts per trillion (ppi). Concentrations of the six PFAS compounds presented in the table were not compared to the new MassDEP standards until the January 2020 monthly system sample collection, which is after the effective date of December 27, 2019.

 4. —A** Concentrations of the three additional PFAS chemicals, PFNA, PFHxS, and PFHpA were not presented prior to 06.11.18. The USEPA Health Advisory only applies to the PFOS and PFOA compounds.

 Concentrations of PFNA, PFHAS, and PFHpA were not presented/abulated until after the MassDEP ORS Guideline was in effect on 06.11.18.

 5. —B** : Concentrations of the PFAS compound, PFDA, were not presented prior to the May 2019 sampling period. On April 19, 2019, MassDEP presented a draft of proposed risk standards for PFAS that included a sixth, PFAS compound, PFDA.

 6. BRIA. —Bellow Laboratory Reporting Limits; reporting limits shown in parentheses.

 7. Concentrations in bold exceed applicable MassDEP ORS Guideline and/or the MCP Method 1 GW-1 groundwater risk standard.

 8. PFOS. Perfluorooctanesulfonic acid

- PFOS Perfluorooctanesulfonic acid
 PFOA Perfluorooctanoic Acid
 PFNA Perfluorononanoic Acid
- PFHXS Perfluorohexanesulfonic Acid
 PFHPA Perfluoroheptanoic Acid
- 13. PFDA Perfluorodecanoic Acid 14. NA - Concentration data not available

Table 1B - Summary of Groundwater Pump and Treatment System Total PFAs Analytical Data -GWTS #2 Barnstable County Fire and Rescue Training Academy 155 Flint Rock Road, Barnstable, MA RTN 4-26179

SAMPLE ID			INFLUEN	Γ (PRW-4)					MIDE	OINT					EFFL	UENT		
USEPA Method 537.2	PFOS (ng/L)	PFOA (ng/L)	PFNA (ng/L)	PFHxS (ng/L)	PFHpA (ng/L)	PFDA (ng/L)	PFOS (ng/L) PFOA (ng/L) PFNA (ng/L) PFHxS (ng/L) PFHpA (ng/L) PFDA (ng/L)							PFOS (ng/L) PFOA (ng/L) PFNA (ng/L) PFHxS (ng/L) PFHpA (ng/L) PFDA (ng/L)				
MassDEP ORS Guidline*			70 ו	ng/L		•			70 i	ng/L					70 г	ng/L		
MCP Method 1 GW-1 Standard ¹⁵			20 ו	ng/L					20 ו	ng/L					20 1	ng/L		
SAMPLE DATE																		
								System Start	up on 11/11/19									
11/12/2019	4200	53	85	200	59	15	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
11/15/2019		-		-			BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
11/19/2019		-		-			BRL (<5.2)	44	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	42	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
12/17/2019 ¹⁶	1500	43	51	180	54	10	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
1/17/2020	2200	57	60	220	69	13	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
2/13/2020	3100	74	66	310	92	17	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)	BRL (<5.2)	BRL (<7.4)	BRL (<4.9)	BRL (<5.2)	BRL (<7.1)	BRL (<4.1)
3/3/2020	3300	72	64	300	81	14	5.6	BRL (<0.23)	BRL (<0.48)	BRL (<0.33)	BRL (<0.37)	BRL (<0.18)	BRL (<0.43)	BRL (<0.23)	BRL (<0.48)	BRL (<0.33)	BRL (<0.37)	BRL (<0.18)
4/28/2020	1900	52	42	210	56	42	64 2.2 1.7 9.7 3.0 0.27							BRL (<0.23)	BRL (<0.48)	BRL (<0.33)	BRL (<0.37)	BRL (<0.18)

Notes:

- 1. Concentrations presented in ng/L nanograms per Liter parts per trillion
- 2. MassDEP's Office of Research and Standards (ORS) expanded upon the USEPA's Health Advisory and created the ORS Guideline that applies to the total summed of five PFAS chemicals, PFOS, PFOA, PFNA, PFNA, PFHxS, and PFHpA, effective June 11, 2018.
- 3. Concentrations of the PFAS compound, PFDA, are presented based on the April 19, 2019, MassDEP draft of new/proposed groundwater standards for PFAS that includes a sixth, PFAS compound, PFDA. However the concentration of PFDA is not include in total PFAS removal calcuations.
- 5. BRL Below Laboratory Reporting Limits; reporting limit shown in parentheses.
- 6. Concentrations in bold exceed applicable MassDEP ORS Guideline
- 7. PFOS Perfluorooctanesulfonic acid
- 8. PFOA Perfluorooctanoic Acid
- 9. PFNA Perfluorononanoic Acid
- 10. PFHxS Perfluorohexanesulfonic Acid

Table

- 11. PFHpA Perfluoroheptanoic Acid
- 12. PFDA Perfluorodecanoic Acid
- 13. --: Concentration data not available and/or sample was not collected on that date.
- 14. Per MCP Regulations, the system was sampled one day, three days, and seven (7) days following the initial week of startup (11/11/19).
- 15. On December 13, 2019, MassDEP published the newly established clean up standards for PFAS in soil and groundwater. These standards were effective as of December 27, 2019 and apply to the total sum of six PFAS chemicals, PFOS, PFOA, PFNA, PFHAS, PFHAS
- 16. The December monthly sample was collected from the system's effluent stream on 12/17/2019 following the receipt of the laboratory results from the 11/19/2019 sampling event on 12/16/2019.

The effluent was resampled again to ensure significant breakthrough was not occurring from the secondary carbon vessel.

Part				Influent Rag Fi	iltor Difforontial	Pre-Filter	Changeout	Post-Filte	er Changeout		INCLUENT	1			FFFILIENT			<u> </u>			
Property Control Con			System								INFLUENT			Т	EFFLUENT	T	ı	_			
Company Comp		Operator ¹	Operating on Arrival	Pre		_		Gauge: P1		Fill Rate (min)	Instantaneous Estimated Influent Flow Rate (GPM) ²		Effluent Flow Rate	Effluent Flow Rate	Totalizer (Gal)	Total Gallons Treated	Flow Rate		on Departure	Sampled	
1. 1. 1. 1. 1. 1. 1. 1.		CE CF		75 94				75 77				1						0.001			· · · · · · · · · · · · · · · · · · ·
Control Cont																					PRW-4 well pump is operating at high level, high level float is not triggering pump to shut off. CS turned off PRW-4 manually at 1243 and restarted at
Proceed Fig. Fig.	4/12/2018	CE	Yes	NA	NA	NA	NA	75	75	2.78	44.0	3						0.002	Yes	No	,
Company Comp	4/13/2018	CE	Yes	88	74	NA	NA	75	74	2.80	43.8	4						0.003	Yes	Yes	Changed 3 bag filters (5 µm) and conducted system pressure checks.
1.	4/16/2018	CE	Yes	86	74			74	74			7							Yes	No	
Second Column					75				7.5												
Property Column Property C																					High level float not triggering PRW-4 to shut down. Sean (B&B Electric) on site to inspect high float electrical issues. PRW-4 shut off at 13:40 to inspect control panel, PRW-4 restarted at 14:55. Transfer pump maintaining flow ahead of PRW-4 well pump. Both carbon vessels backwashed. Changed 3 bag
Control Cont	4/24/2018	CE	Yes	74	NA	NA	NA	76		3.18	38.5	15			-			0.009	Yes	No	
Control Cont		CE	Yes	79	NA	NA	NA	75		3.30	37.1	16						0.009	Yes		
Control Cont																					
No. Column Colu																					
Second Control Contr	., 30, 2010								,,,	5.55									.03	.10	
1.50 1.50	5/1/2018	CS	Yes	83		NA	NA	75		3.83	32.0	0.00						0.0000	Yes	No	Adjusted /increased VFD of transfer pump from 35 psi to 40 psi to maintain drawdown ahead of PRW-4 well pump. No bag change. 1" drawdown ~ 1:41
17.50 17.5																					
Section Sect																					· · · · · · · · · · · · · · · · · · ·
	3/1/2010			110	73	INA	INA	/4	74	3.7				-			-		163	140	Changed 3 bag filters (5 um) and conducted system pressure checks.
1	6/5/2018	CE/MM	No		-	NR	NR	NR	NR			0				-		0			Carbon Change out- filled vessels with water and let to sit for ~24 hours, changed 3 bag filters (5 um)
A												1			-						
CC2/2003 CC																					ÿ , i ÿ ,
Section Sect							NR	NR		3.68		7						0.004			
## Section Property Property				58	54			_		3.46	35.4							0.005	Yes		
March Marc				77	60			_													
Part																					
Control Cont	6/20/2018	CE	Yes	72	60	NR	NR	NR	NR	3.73	32.8	15						0.008	Yes	No	
625-777-18 C. Yes														==							speed.
627/2018 C. Ves		OL.												==	-	==					
Total Superior Total Superior Total Superior Total Superior																					
7/2/2018 CE	6/29/2018			78	68	NR	NR	NR	NR	3.68									Yes	No	Changed 3 bag filters, conducted system pressure checks.
175/2018 CE No NR NR NR NR NR NR NR	7/2/2018			83	60	ND	NID	NID	NID	3 05									Voc	No	Changed 2 has filters conducted system pressure chacks
71/2018 CE																					
711/12/10 CE	7/6/2018	CE	Yes			NR	NR	NR	NR												Changed 3 bag filters, conducted system pressure checks.
7.1742/078 CE												-									
7/18/2018 CE Yes 98 70 NR NR NR NR NR NR NR N												10									
17/19/2018 CE Yes 94 77 NR NR NR NR NR NR NR												15									
17/20/2018 CE Yes 81 72 NR NR NR NR NR NR NR N																					
7/23/2018 CE										4.03	30.4	17				.		0.008			
17/25/2018 CE								_		4.47	27.4	21						0.009			
7/21/2018 CE	7/25/2018							NR													
7/30/2018 CE											-		-		-	-		-			
Totals - July 2018 CE													-								
8/6/2018 CE Yes 94 72 NR NR NR NR NR 5.22 23.5 6	1130/2010			71	71	1417	INIX	IVIC	INIX	4.70			-		-				162	IVU	onangoa o sag mors, sorradorea afaren pressar e areato.
8/10/2018 CE Yes 98 72 NR NR NR NR NR NR 4.32 28.4 10																					
8/14/2018 CE Yes 82 69 NR NR NR NR NR NR NR 4.8 25.5 14 0.007 Yes No Changed 3 bag filters, conducted system pressure checks. 8/17/2018 CE Yes 81 64 NR NR NR NR NR NR NR 5.0 24.5 17 0.008 Yes No Changed 3 bag filters, conducted system pressure checks. Backwashed carbon vessels. 8/21/2018 CE No 78 68 NR NR NR NR NR NR 5.2 23.6 20 0.009 Yes No Reavery well down, due to contactor burnout/failure. System restarted at 14:45. 8/24/2018 CE Yes 89 69 NR NR NR NR NR NR NR NR 6.03 20.3 27 0.011 Yes No Changed 3 bag filters, conducted system pressure checks.																					
8/17/2018 CE Yes 81 64 NR NR NR NR NR NR 5.0 24.5 17 0.008 Yes No Changed 3 bag filters, conducted system pressure checks. Backwashed carbon vessels. 8/21/2018 CE No 78 68 NR NR NR NR NR NR NR 5.2 23.6 20 0.009 Yes No Recovery well down, due to contactor burnout/failure. System restarted at 14:45. 8/28/2018 CE Yes 89 69 NR NR NR NR NR NR NR NR 0.03 20.3 27 0.011 Yes No Changed 3 bag filters, conducted system pressure checks.													-		-						
8/24/2018 CE Yes 77 68 NR NR NR NR NR NR S.32 23.0 23 0.010 Yes No Changed 3 bag filters, conducted system pressure checks. 8/28/2018 CE Yes 89 69 NR NR NR NR NR NR 0.03 20.3 27 0.011 Yes No Changed 3 bag filters, conducted system pressure checks.	8/17/2018		Yes	81	64	NR	NR	NR	NR	5.0	24.5	17						0.008	Yes	No	Changed 3 bag filters, conducted system pressure checks. Backwashed carbon vessels.
8/28/2018 CE Yes 89 69 NR NR NR NR NR NR 6.03 20.3 27 0.011 Yes No Changed 3 bag filters, conducted system pressure checks.																.					
100,0	5. 25, 25.5		Tab;e							2.00	24.1	30						0.014		.,,,	y yy

1968 3.	K11N 4-20177																					
March Marc												INFLUENT				EFFLUENT						
Column C	Date	Opera	ator ¹ Opera	ating on	Pre	Post	Gauge: P1	Gauge: P2	Gauge: P1	Gauge: P2		Instantaneous Estimated Influent		Effluent Flow Rate	Effluent Flow Rate	Totalizer (Gal)	Total Gallons Treated	Flow Rate				Comments
Color Colo	9/4/2018			/es			_						4				-				No	
The color The		_											7									
Control Cont																						
1																						
1. 1. 1. 1. 1. 1. 1. 1.	9/21/2018																					
Second Column	9/24/2018	CE	Y	/es	94	70	NR	NR	NR	NR	8.03	15.3	23						0.010	Yes	No	
1	9/28/2018						NR	NR	NR	NR												Carbon Change out- filled vessels with water and let to sit for ~24 hours, changed 3 bag filters (5 um), system sampled on 09/27/18.
Control Cont	10/1/2019	_			70	E7	ND	I ND	ND	I ND	E 02		28							Voc	No	Sustain restarted after eshadulad shutdown for earbon evokanea. Changod 2 han fill are, conducted sustain procesure shocks
1982 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.		_											5				-					
Marie Mari	10/10/2018												10									
No. 10				/es									12								No	U U ,
Control Cont		_																				
Control Cont																						
Second Column C																						
No. Proceedings Proceedi																						
No. 1		Tota	als - October	2018								17.4	31						0.011			
No. 1	11/2/2018	CF	Y	/es	71	62	NR	NR	NR	NR	7.86	15.6	2				-		0.001	Yes	No	Changed 3 bag filters, conducted system pressure checks.
160971 100971 1	11/6/2018	CE	Y	/es	71	62	NR	NR	NR	NR			6							No	No	Changed 3 had filters, conducted system pressure checks. Rackwashed both carbon vessels. System shutdown at 10:00 for force main decealing and flush
1.65991 7	11/8/2018	CF	E V	/es	65	45	NR	NR	NR	NR	5.25	23.3	6						0.004	Yes	No	
1962 1.6 1.	11/9/2018	_											7									
1. 1. 1. 1. 1. 1. 1. 1.	11/12/2018	CE	Y	/es	51	47	NR	NR	NR	NR	5.03	24.4	10						0.007	Yes	No	
1965 1966	11/13/2018																					
1969 G		_										24.9							0.008			
1968 1												 24 E							0.010			
Control Cont		_																				
Water Wate	11/27/2018	_															-					
19/2016 19	11/30/2018	CE	Y	/es	77	58	NR	NR	NR	NR	5.85		28				=			Yes	No	Changed 3 bag filters, conducted system pressure checks.
17-7-17-17-17-17-17-17-17-17-17-17-17-17								,														
1													3									
24 15													11									
1977 1978	12/14/2018	_																				
12-20-20-20-20-20-20-20-20-20-20-20-20-20	12/18/2018	CE	E Y	/es	70	65	NR	NR	NR	NR	6.72	18.2	18						0.004	Yes	No	Changed 3 bag filters, conducted system pressure checks.
1976/1976 7	12/21/2018																					
1																						
Teach Provided P		_																				
1909 98	12/31/2016				02	/1	INK	INK	IVIX	IVI	7.30									162	INU	Crianged 3 day filters, conducted system pressure checks.
1700 1700	1/4/2019				72	72	NR	NR	NR	NR	6.5									Yes	No	Changed 3 bag filters, conducted system pressure checks, observed hole in pre-filter basket.
11/10/10 Ves	1/7/2019	PC	В У	/es				NR					<u> </u>				=			Yes	No	
11/10/2019 PK3																						
11/5/2019 P.S. Yes P.S.																			0.003			
1/18/2017 Fig. F																						, ,
12/12/12/12/12/12/12/12/12/12/12/12/12/1		_		_							8.65	14.2							0.004			
17/17/2019 SCI Yes 88 68 NR NR NR NR NR NR NR N	1/21/2019	SC	T Y	/es	80		NR	NR	NR	NR	8.15	15.0							0.005	Yes		Change 3 bag filters, conducted system pressure checks.
1/10/2019 P.G. Yes 8.6 71 N.B.										_												
19/12/19/19 PGB PG																						
Total Junuary 2019 Ves. 0	4 /04 /0040	- 00		,	0.0		ND	NO			9	13.6	30				-		0.007	.,		
24/22/19 FF Yes	1/31/2019				03	- / 1	(VIX	I WIN	IVIX	IVIX		14.5	31						0.008	163	140	
2717/2019 PCB	2/4/2019						NR	NR		NR											No	Carbon Change out- filled vessels with water and let to sit for ~24 hours, changed 3 bag filters (5 um).
2/3/2019 ST Ves 55 43 NR															222.7				0.002			
2/15/2019 M/M	2/11/2019																					
22222019 ST Yes - - NR NR NR NR NR NR					55	43									131 7	-	-		0.007			
2/25/2019 MDM Yes 25 15 NR NR NR NR NR NR NR N							_															
Totals - February 2019					25	15																
3/3/2019 ST Yes 45 40 NR															132.7				0.011			
3/3/2019 PCB/ST Yes 46 40 NR	3/1/2019										7.55	16.2	1		76.6				0.001			
3/7/2019 PCB/ST Yes 50 40 NR		_											3									
3/9/2019 ST Yes 44 41 NR												 15.0										
3/11/2019 ST Yes 58 50 NR							_															
3/13/2019 ST Yes 65 50 NR		_													68.1							
3/16/2019 PCB No 62 60 NR	3/13/2019	ST							NR		4.62	26.5										Noticed low speed on transfer pump, adjusted VFD to increase pump speed to 55 Hz. Changed 3 bag filters twice.
No No No No No No No No	3/14/2019	ST	Г	/es	75	50	NR	NR	NR	NR	5.16	23.7	14		70.0	-	-		0.012	Yes	No	
3/22/2019 ST Yes 28 20 NR	3/16/2019	PC	B	No	62	60	NR	NR	NR	NR			15							Yes	No	Pump at PRW-4 shut off upon arrival to system, contact relay failure, possibly due to power surge from thunderstorm. Restarted system after contact relay
3/23/2019 ST Yes 23 20 NR												E4 F			E1 F				0.020			· ·
3/29/2019 RPT/ST No											2.38	51.5			51.5				0.038			
3/29/2019 RPT/ST No NR NR NR NR NR 23 Yes No Removed/pumped out the contents of the influent equalization (EQ) tank, repaired the system's pump electrical components, adjusted VFD on transfer pump, installed unions on influent piping manifold, replaced bag filters at discharge into the EQ tank, and restarted the system at 1645.	3/23/2019	ST	Г Ү	/es	23	20	NR	NR	NR	NR			22							No	No	
3/29/2019 RP1/S1 NO NR NR NR NR NR NR			_					1					1							1		
	3/29/2019	RPT	/ST N	No			NR	NR	NR	NR			23							Yes	No	
Totals - March 2019 29.3 25 63.2 0.022																						parity, instance unions on innuerit piping mannout, repraces paginters at uistifalige into the EQ talik, and restalled the system at 1045.
		To	tais - March 2	2019								29.3	25		63.2				0.022			

			Influent Bag Fi			Changeout Pressure (psi)		r Changeout Pressure (psi)		INFLUENT				EFFLUENT						
Date	Operator ¹	System Operating on Arrival	Pre	Post	Gauge: P1	Gauge: P2	Gauge: P1	Gauge: P2	6" Influent Tank Fill Rate (min)	Combined Instantaneous Estimated Influent Flow Rate (GPM) ²	Days System Operating	Instant. Effluent Flow Rate (GPM) ⁸	Instantaneous Effluent Flow Rate (GPM) ^{2,9}	Totalizer (Gal)	Total Gallons Treated	Average Effluent Flow Rate (GPM) ¹⁰	Estimated Total PFAs t Removal (kg) ³	System Operating on Departure	System Sampled	Comments
4/1/2019	ST	Yes			40	28	40	39	2.25	54.4	1						0.002	Yes	No	Conducted system pressure checks and changed bag filters.
4/3/2019 4/6/2019	ST ST	Yes			40 50	39 41	50	50	2.23	54.9	6						0.014	Yes Yes	No No	Conducted system pressure checks. Conducted system pressure checks and changed bag filters.
4/9/2019	GWTT	Yes			40	50			1.6	76.6	9		18.85				0.029	Yes	Yes	Conducted system pressure checks, backwashed the primary carbon vessel for ~30 minutes; inspected the transfer pump and removed excess iron oxide sedimentation from the inlet piping.
4/10/2019	ST	Yes			50	15	23	25			10							Yes	No	Conducted system pressure checks and changed bag filters.
4/11/2019	ST	Yes			40	35	35	35			11							Yes	No	Conducted system pressure checks and changed bag filters.
4/12/2019	GWTT	Yes			50	40	44	46	3	40.8	12						0.020	Yes	No	Conducted system pressure checks and changed bag filters. Conducted system pressure checks and changed bag filters.
4/15/2019 4/19/2019	GWTT	Yes Yes			55 58	45 55	55 35	55 40	4.08 2.5	30.0 49.0	15 19					-	0.019 0.039	Yes Yes	No No	Conducted system pressure checks and changed bag filters. Conducted system pressure checks and changed bag filters.
4/23/2019	GWTT	Yes			48	47	50	55	4.00	30.6	23		33.4			-	0.029	Yes	No	Conducted system pressure checks and changed bag filters.
4/26/2019	GWTT	Yes			58	50	55	60			26		20.3					Yes	No	Conducted system pressure checks and changed bag filters, conducted general housekeeping duties.
4/30/2019	GWTT	No								==	29								Yes	System off on arrival due to contact relay failure for transfer pump operation; system restarted at 16:29 after contact relay was replaced.
	Totals	- April 2019						<u> </u>		48.1	29		24.2				0.058			
5/3/2019	GWTT	Yes			55	35	45	50	2.18	56.2	3		32.93				0.003	Yes	No	Conducted system pressure checks and changed bag filters.
5/7/2019	GWTT	Yes			58	38	50	55	2.05	59.8	7		31.57				0.007	Yes	No	Conducted system pressure checks and changed bag filters.
5/10/2019	GWTT	No								==										System down as a result of failed VFD for transfer pump operation, changed bag filters.
5/17/2019	GWTT	No			55	38					10	-						Yes	No	Installed new VFD drive, system shutdown due to power surge from thunderstorm. Electrician added 15 minute- electrical control delay at the control panel in the system shed: creating a 15 minute delay before the pump at PRW-4 powers on at the "high level" float switch.
5/21/2019	MDM	No			57	30	57	60	1.83	66.9	14		33.38			1	0.016	Yes	Yes	Power surge from roque ground voltage at electrical easement "fried" the electrical delay at control panel in system shed. Electrican bypassed delay to allow system restart at 11:15. Electrician will change coil at PRW-4 panel to lower voltage at later date. Conducted system pressure checks and changed bag filters.
5/24/2019	GWTT	Yes	I T		58	35	58	60	2.083	58.8	17		25.36				0.017	Yes	No	Conducted system pressure checks and changed bag filters. Bypass installed to allow 15 minute delay on PRW-4 submersible pump float switch.
5/28/2019	GWTT	Yes			56	46	55	60	2.65	46.2	21		52.10				0.016	Yes	No	Conducted system pressure checks and changed bag filters twice. Backwashed both carbon vessels.
5/31/2019	GWTT	Yes			58	35	55	60	2.17	56.5	24		36.90				0.022	Yes	No	Conducted system pressure checks and changed bag filters, 3" butterfly valve on INF of LGAC\$ #2 replaced. Installed a 3 inch flow totalizer and meter on
		- May 2019								57.4	24		35.4				0.023			
6/4/2019	GWTT	Yes			57	48	57	62	2.46	49.8	4		20.2			1	0.010	Yes	No	Conducted system pressure checks and changed bag filter. Replaced in-kind flow meter previously installed on 5/31/19.
6/7/2019	GWTT	Yes			57	45	57	62	2.43	50.4	7		16.2				0.017	Yes	No	Conducted system pressure checks and changed bag filters.
6/11/2019	GWTT	Yes			76	78	70	82	2.53	48.4	11		17.3				0.026	Yes	No	Conducted system pressure checks and changed bag filters. System shutdown due to high pressure measurement on the LGAC vessels, (from iron fouling): carbon change to occur on 6/13/19.
6/13/2019	MDM	No									11							No	No	System off for carbon change out.
6/14/2019	GWTT	No					25	28	2.3	53.3	12		167.1				0.032	Yes	No	System restarted at 13:00; adjusted flow rate via VFD to 55 Hz. GWTT recorded Effluent flow rate from drop in site glass to be 44 seconds, immediately after adjusting the VFD.
6/18/2019	GWTT	Yes			25	10	11	15	2.23	54.9	16		56.2				0.043	Yes	No	Gonducted system checks, changed bag filters, adjusted VFD to 55 GPM.
6/21/2019	GWTT	Yes			17	15	17	20	2.12	57.8	19		58.6				0.054	Yes	No	Conducted system checks, changed bag filters, adjusted VFD to 28 Hz.
6/25/2019	GWTT	Yes			20	18	20	25	2.3	53.3	23		59.0				0.060	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 28 to 35 Hz.
6/27/2019	MDM	Yes Yes			33	21 22	30	35	3.2 2.4	38.3 51.0	25 26		17.5 60.9				0.047 0.065	Yes Yes	Yes No	Conducted system checks, system VFD at 35 Hz; pressure gauges at LGAC 2 are 0 psi. Conducted system checks, changed bag filters, VFD at 35 Hz. Effluent flow rate increased after bag filter changeout.
0/20/2019		- June 2019			- 33		30	35	2.4	50.8	27		62.4		NR ¹¹		0.068	163	140	conducted system diseas, changed bag inters, vi D at 35 Hz. Embert now rate indeased arter bag inter-changeout.
7/2/2019	GWTT	Yes			32	20	30	32	2.52	48.6	2	NR	52.6	20575			0.005	Yes	No	Conducted system checks, changed bag filters.
7/5/2019	GWTT	Yes			25	23	30	35	2.53	48.4	5	NR	52.6	242970	222395		0.013	Yes	No	Conducted system checks, changed bag filters, VFD at 35 Hz. Effluent flow rate increased after bag filter changeout.
7/9/2019 7/12/2019	GWTT	Yes			32 39	25 35	36 39	40 43	2.35 2.42	52.1 50.6	9 12	NR NR	58.6 55.7	311680 407920	68710 96240		0.026 0.033	Yes	No No	Conducted system checks, changed bag filters, VFD at 35 Hz. Effluent flow rate increased after bag filter changeout. Primary LGAC vessel requires a Conducted system checks, changed bag filters, adjusted VFD to 42 Hz.
7/15/2019	GWTT	Yes			46	40	35	50	3.00	40.8	15	NR	55.7	587740	179820		0.033	Yes	No	Conducted system checks, changed bag filters, adjusted VFD for 42 Hz. Conducted system checks, changed bag filters, adjusted VFD from 42 Hz to 40 Hz.
7/18/2019	GWTT	Yes			45	28	55	60	2.83	43.3	18	NR	47.48	NR	NR		0.043	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 40 Hz to 45 Hz.
7/23/2019	GWTT	Yes			56	43	55	61	3.22	38.0	23	NR	25.63	717580	129840		0.048	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 40 Hz to 45 Hz.
7/26/2019	GWTT	Yes			56	50	56	60			26	NR	11.93	722700	5120			Yes	No	Conducted system checks, changed bag filters.
7/29/2019	GWTT	Yes					56	60	2.50	49.0	29	NR	53.3	723360	660		0.078	Yes	Yes	Pumped out contents of exterior totes and conducted backwash of system (6,800 gallons removed by Global). Shutdown system for ~2 hours. VFD at 23 H on departure.
	Totals	- July 2019								46.9	31		45.1		NR ¹¹		0.079			
8/2/2019					15	5	18	9	2.68	50.6	2	NR	19.68	723960	0	0.0	0.006	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 23 Hz to 28 Hz.
8/5/2019	GWTT	Yes			21	8	16	20	2.50	52.8	5	NR	49.00	726280	2320	0.5	0.014	Yes	No	Conducted system checks, changed bag filters, VFD at 28 Hz.
8/8/2019	GWTT	Yes			20	19	22	27	2.23	54.9	8	NR	53.50	729450	3170	0.7	0.024	Yes	No	Conducted system checks, changed bag filters, adjusted VFD to 32 Hz and 31 Hz. Visability of site glass impaired due to iron fouling, possible obstruction in site glass causing error in flow calculations.
8/13/2019	GWTT	Yes			27	23	28	30	2.17	56.5	13	NR	56.45	738390	8940	1.2	0.040	Yes	No	Conducted system checks, changed bag filters, adjusted VFD to 23 Hz. Obstruction in site glass seems apparent, affecting flow rate calculations.
8/16/2019	GWTT	Yes			32	26	30	35	1.04	117.8	16	NR	34.83	744020	5630	1.3	0.103			Conducted system checks, changed bag filters, adjusted VFD from 23 Hz to 28 Hz.
8/20/2019	GWTT	Yes			40	27	36	38	NR	NR	20	NR	NR	757990	13970	2.4		Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 38 Hz to 39 Hz. Could not calculate influent flow rate due to obstruction in site glass
8/23/2019	GWTT	Yes			41	29	38	44			23	NR	50.00	790720	32730	7.6	0.063	Yes	Yes	Conducted system checks, changed bag filters, and adjusted VFD from 39 Hz to 40 Hz. Collected monthly system samples on 8/22/19.
8/27/2019	GWTT	Yes			45	35	44	49			27	NR ND	50.00	873750	83030	14.4	0.074	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 40 Hz to 42 Hz.
8/30/2019		Yes August 2019		-	49	37	8	10		66.5	30 31	NR	49.00 NR ¹¹	976540	102790 252580	23.8 6.5	0.081 0.113	Yes	No	Conducted system checks, changed bag filters after backwash of primary vessel.
9/3/2019	GWTT	Yes	- I		18	7	10	14	NA	NA	3		NR	1044190	67650	15.7	0.001	Yes	No	Conducted system checks, changed bag filters, "High High Level" Alarm indicated, adjusted VFD, site glass plugged due to iron oxide sludge build up at
9/6/2019	GWTT	Yes			27	14	22	25	NA	NA	6		NR	NR	NR	NR		Yes	No	bottom of EQ tank, could not collect influent flow rate. Conducted system checks, changed bag filters, "High High Level" Alarm indicated, adjusted VFD to 35 Hz from 31 Hz.
9/10/2019	GWTT	Yes			35	18	30	35	NA	NA	10		NR	1203690	159500	27.7	0.008	Yes	No	
9/13/2019	GWTT	Yes			40	25	40	42	NA	NA	13		NR	1311290	107600	24.9	0.009	Yes	No	Conducted system checks, changed bag filters, observed approximately 20 in. of sludge in EQ Tank, and adjusted VFD to 40 Hz from 38 Hz.
9/16/2019	GWTT	Yes			45	26	44	48	NA	NA	16		NR	1413970	102680	23.8	0.011	Yes	No	Conducted system checks, changed bag filters, and adjusted VFD to 48 Hz.
9/20/2019	GWTT	Yes			68	35	12	14	NA	NA	20	-	NR	1543040	129070	22.4	0.013	Yes	No	Conducted system checks, changed bag filters, backwashed primary GAC vessel, and adjusted VFD to 29 Hz.
9/23/2019	GWTT	Yes			24	8	23	27	NA	NA	23		NR	1563850	20810	4.8	0.003	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 29 Hz to 34 Hz.
										NIA	. 27		NR	1577890	14040	2.4	0.002	Yes	No	
9/27/2019	GWTT	Yes eptember 2019 ¹²			32	17	42	44	NA	NA NA ⁷	27 30		NR ¹¹	13//090	601350	17.4	0.002	163	INU	Conducted system checks, changed bag filters, adjusted VFD from 34 Hz to 42 Hz, system samples collected on 9/26/19.

				Iter Differential		Changeout Pressure (psi)		r Changeout Pressure (psi)		INFLUENT				EFFLUENT						
Data O	1 -	System	Pressur	e (psi)					6" Influent Tank	Combined	Days System	Instant.					Estimated Total PFAs	System Operating	System	C
Date Opera		erating on Arrival	Pre	Post	Gauge: P1	Gauge: P2	Gauge: P1	Gauge: P2	Fill Rate (min)	Instantaneous	Operating	Effluent	Instantaneous Effluent Flow Rate	Totalizer (Gal)	Total Gallons Treated	Average Effluent Flow Rate	Removal (kg) ³	on Departure	Sampled	Comments
				. 650	oddgo. i i	oddgo.12	Caage. 1 1	oddgo.12		Estimated Influent Flow Rate (GPM) ²		Flow Rate (GPM) ⁸	(GPM) ^{2,9}	Totalizor (oul)	Total Gallons Houtou	(GPM) ¹⁰				
										,		,								Conducted system checks, changed bag filters, adjusted VFD from 42 Hz to 31 Hz. Operator noticed a loud sound on discharge pipes at LGAC #1 as well as
10/1/2019 GW		Voc			50	20	18	19	NA	NA	1		NR	1420400				Voc	No	a pressure drop across the entire system, system was instantly turned off and restarted after the VFD was adjusted. Operator assumed an obstruction (i.e.
10/1/2019 GW	'' '	Yes			50	28	10	19	INA	INA	'		IVK	1620400	-			Yes	No	iron oxide precipitates) was in LGAC#1 restricting flow and loud sound was the obstruction being dislodged.
																				System was shut off at 8:00 during excavation of the effluent discharge piping. The discharge piping was repaired and the system was restarted at 16:00.
10/3/2019 GW	TT Y	Yes							NA	NA	3		NR	1639940	19540	6.8	0.0005	Yes	No	The bag filters were changed.
10/7/2019 GW		Yes			27	14	22	20	NA	NA NA	6		NR	1645550	5610	1.3	0.0002	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 31 Hz to 35 Hz. Conducted system checks, changed bag filters, adjusted VFD from 35 Hz to 32 Hz.
10/11/2019 GW 10/15/2019 GW		Yes			32 29	30 20	19 27	20 30	NA NA	NA NA	10 14		NR NR	1683870 1755270	38320 71400	6.7 12.4	0.0015 0.0040	Yes Yes	No No	Conducted system checks, changed bag filters, adjusted VFD from 32 Hz to 39 Hz.
10/18/2019 GW		Yes			38	22	30	35	NA	NA	18		NR	1867270	112000	19.4	0.0082	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 39 Hz to 35 Hz.
10/22/2019 GW		Yes			34	13	31	35	NA	NA	21		NR	1946590	79320	18.4	0.0090	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 35 Hz to 43 Hz.
10/25/2019 GW	11 1	Yes			44	34	35	42	NA	NA	24		NR	2043780	97190	22.5	0.0126	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 43 Hz to 40 Hz. Conducted system checks, changed bag filters, Global Cycle on site to vacuum pump out the contents from the EQ tank, bag filter unit, totes containing
10/28/2019 GW	TT Y	Yes			44	34	35	42	5.38	22.8	27		NR	2123880	80100	18.5	0.0117	Yes	No	water from GAC vessel backwashes. The VFD was adjusted from 40 Hz to 24 Hz. Pressure gauge at P5 was replaced. System sampled on 10/30/19.
T.	1 0 1 1 1	224212								7	20		11		502400	11.7	0.000			
11/1/2019 GW	als - October 2	Yes			15	2	19	19	5.00	NA ⁷ 24.5	30	NR	NR ¹¹ 53.26	2128040	503480 4160	11.7 2.9	0.008	Yes	No	Conducted system checks, changed bag filters, and adjusted the VFD frequency.
11/4/2019 GW		Yes			26	8	21	17	4.28	28.60	4	NR	45.37	2131870	3830	0.9		Yes	No	Conducted system checks, changed bag filters, and the VFD was adjusted from 30 Hz to 29 Hz.
11/7/2019 GW	TT \	Yes			25	10	30	27	3.70	33.1	7	NR	44.0	2042122				Yes	No	Conducted system checks, changed bag filters, exchanged 3" flow meter to 2" pulse turbine flow meter/totalizer. Adjusted the VFD from 29 Hz to 34 Hz on
																				departure. Conducted system checks, changed bag filters, VFD left at 34 Hz. Force main Influent flow was split; temporary GWTPS expansion system started. System
11/11/2019 GW	TT Y	Yes			32	18	31	35	3.70	33.1	11	35	NR	2119390	77268	13.4	0.0037	Yes	Yes	sampled on 11/12/19.
11/15/2019 GW		Yes			32	21	32	36	4.47	27.4	14	43	NR	2190828	71438	16.5	0.0058	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 34 Hz to 38 Hz on departure.
11/18/2019 GW 11/22/2019 GW		Yes Yes			40 42	30 27	42 41	46 45	4.43 3.50	27.6 35.0	17 21	37 33	NR NR	2273202 2391315	82374 118113	19.1 20.5	0.0081 0.0108	Yes Yes	No No	Conducted system checks, changed bag filters, adjusted VFD from 38 Hz to 39 Hz upon departure. Conducted system checks, changed bag filters. VFD kept at 39 Hz. Cleared sludged out of bottom of sight glass on EQ tank.
11/25/2019 GW		Yes			43	32	43	46	3.90	31.4	24	42	NR	2486658	95343	22.1	0.0133	Yes	No	Conducted system checks, changed bag filters. VFD kept at 39 Hz.
11/29/2019 GW		Yes			45	32	44	48	4.10	29.9	28	39	NR	2601976	115318	20.0	0.0141	Yes	No	Conducted system checks, changed bag filters.
		er 2019 12	Т		1	1	1	T		30.1	29		NR ¹¹	2405000	559854	21.6	0.016			Sustam shutdaum at 10:00 for force main de code process
12/2/2019 BET	ΓA \	Yes									2			2685088	83112	28.9	0.016 0.001	No	No	System shutdown at 10:00 for force main de-scale process. Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process.
	ΓA \						 52	60	4.55	30.1 26.9			NR ¹¹ NR	2685088 2685088			0.016			System shutdown at 10:00 for force main de-scale process. Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart.
12/2/2019 BET	AT AT	Yes			 55	25	52 52	60	4.55 2.17		2	 50			83112	28.9	0.016 0.001	No	No	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW	TA Y	Yes No Yes			55		52	58	2.17	26.9	2	50	NR NR	2685088 2735900	83112 0 50812	28.9 0.0 17.6	0.016 0.001 0.000 0.001	No Yes Yes	No No No	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon
12/2/2019 BET 12/4/2019 BET	TA Y	Yes No				 25				26.9	2		 NR	2685088	83112 0	28.9 0.0	0.016 0.001 0.000	No Yes	No No	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW	A Y A A A A A A A A A A A A A A A A A A	Yes No Yes			55		52	58	2.17	26.9	2	50	NR NR	2685088 2735900	83112 0 50812	28.9 0.0 17.6	0.016 0.001 0.000 0.001	No Yes Yes	No No No	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW	FA Y	Yes No Yes Yes			55 59	22	52 58	58	2.17 2.12	26.9 62.0	2 2 4 7	50	NR NR NR	2685088 2735900 2854135.0	83112 0 50812 118235	28.9 0.0 17.6 27.4	0.016 0.001 0.000 0.001 0.002	No Yes Yes	No No No No	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW	TA I I I I I I I I I I I I I I I I I I I	Yes No Yes Yes Yes Yes Yes			55 59 64 66	22 66 70	52 58 45 56	58 63 71 74	2.17 2.12 1.95 2.02	26.9 62.0 62.0 62.8 60.6	2 2 4 7 11	50	NR NR NR 48.0	2685088 2735900 2854135.0 3002260.0 3122091.0	83112 0 50812 118235 148125 119831	28.9 0.0 17.6 27.4 25.7 27.7	0.016 0.001 0.000 0.001 0.002 0.003 0.004	No Yes Yes Yes Yes Yes Yes	No No No No No Yes	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW	TA I I I I I I I I I I I I I I I I I I I	Yes No Yes Yes Yes			55 59 64	22 66	52 58 45	58 63 71	2.17 2.12 1.95	26.9 62.0 62.0	2 2 4 7	50	NR NR NR 48.0	2685088 2735900 2854135.0 3002260.0	83112 0 50812 118235 148125	28.9 0.0 17.6 27.4 25.7	0.016 0.001 0.000 0.001 0.002 0.003	No Yes Yes Yes Yes Yes	No No No No	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW	TA YA TA	Yes No Yes Yes Yes Yes Yes			55 59 64 66	22 66 70	52 58 45 56	58 63 71 74	2.17 2.12 1.95 2.02	26.9 62.0 62.0 62.8 60.6	2 2 4 7 11	50	NR NR NR 48.0	2685088 2735900 2854135.0 3002260.0 3122091.0	83112 0 50812 118235 148125 119831	28.9 0.0 17.6 27.4 25.7 27.7	0.016 0.001 0.000 0.001 0.002 0.003 0.004	No Yes Yes Yes Yes Yes Yes	No No No No No Yes	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW	TA I I I I I I I I I I I I I I I I I I I	Yes No Yes Yes Yes Yes Yes Yes Yes Yes			55 59 64 66 45 NR	22 66 70 63 NR	52 58 45 56 41 NR	58 63 71 74 67 NR	2.17 2.12 1.95 2.02 NR NR	26.9 62.0 62.0 62.8 60.6 NR	2 2 4 7 11 14 18	50	NR NR NR 48.0 40.0 16.00 NR	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0	83112 0 50812 118235 148125 119831 116984	28.9 0.0 17.6 27.4 25.7 27.7 20.3	0.016 0.001 0.000 0.001 0.002 0.003 0.004	Yes Yes Yes Yes Yes Yes No	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 pl.; Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters,
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/23/2019 GW 12/23/2019 GW		Yes No Yes Yes Yes Yes Yes Yes No No			55 59 64 66 45 NR	22 66 70 63 NR	52 58 45 56 41 NR	58 63 71 74 67 NR	2.17 2.12 1.95 2.02 NR NR 2.25	26.9 62.0 62.0 62.8 60.6 NR NR	2 2 4 7 11 14 18 21 22	50	NR NR NR NR 48.0 40.0 16.00 NR NR	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0	83112 0 50812 118235 148125 119831 116984 78297	28.9 0.0 17.6 27.4 25.7 27.7 20.3	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004	No Yes Yes Yes Yes Yes Yes No Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/23/2019 GW 12/26/2019 GW 12/30/2019 GW	Name	Yes No Yes			55 59 64 66 45 NR	22 66 70 63 NR	52 58 45 56 41 NR	58 63 71 74 67 NR	2.17 2.12 1.95 2.02 NR NR	26.9 62.0 62.0 62.8 60.6 NR NR 54.4	2 2 4 7 11 14 18 21 22 26	50	NR NR NR 48.0 40.0 16.00 NR NR NR	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0	83112 0 50812 118235 148125 119831 116984 78297	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006	Yes Yes Yes Yes Yes Yes No	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 pl.; Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters,
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/23/2019 GW 12/26/2019 GW 12/26/2019 GW Totals	TA YA ITA ITA YA	Yes No Yes			55 59 64 66 45 NR NR 19	22 66 70 63 NR 11	52 58 45 56 41 NR NR	58 63 71 74 67 NR 14	2.17 2.12 1.95 2.02 NR NR 2.25 2.42	26.9 62.0 62.0 62.8 60.6 NR NR 54.4	2 2 4 7 11 14 18 21 22 26 27	50	NR NR NR 48.0 40.0 16.00 NR NR S2.00 39.0	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.012 0.006 0.006	Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, VFD at 26 Hz.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/23/2019 GW 12/26/2019 GW 12/30/2019 GW Totals 1/3/2020 GW	TA YA ITA	Yes No Yes			55 59 64 66 45 NR NR 19	22 66 70 63 NR 11 11	52 58 45 56 41 NR NR 6	58 63 71 74 67 NR 14 13	2.17 2.12 1.95 2.02 NR NR 2.25 2.42	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8	2 2 4 7 11 14 18 21 22 26 27 3	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001	Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00 .Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, when adjusted VFD.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/26/2019 GW Totals 1/3/2020 GW 1/6/2020 GW	TA YA I I I I I I I I I I I I I I I I I I	Yes No Yes			55 59 64 66 45 NR NR 19	22 66 70 63 NR 11 11	52 58 45 56 41 NR NR 6	58 63 71 74 67 NR 14 13	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0	2 2 4 7 11 14 18 21 22 26 27 3 6	50		2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864 104471	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001 0.002	Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/23/2019 GW 12/26/2019 GW 12/30/2019 GW Totals 1/3/2020 GW	TA	Yes No Yes			55 59 64 66 45 NR NR 19	22 66 70 63 NR 11 11	52 58 45 56 41 NR NR 6	58 63 71 74 67 NR 14 13	2.17 2.12 1.95 2.02 NR NR 2.25 2.42	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8	2 2 4 7 11 14 18 21 22 26 27 3	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001	Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00 .Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, when adjusted VFD.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/13/2019 GW 12/20/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/23/2019 GW 12/30/2019 GW 1/3/2020 GW 1/10/2020 GW 1/13/2020 GW	TA YA I I I I I I I I I I I I I I I I I I	Yes No Yes			55 59 64 66 45 NR NR 19 18 18 21 21	22 66 70 63 NR 11 11 11 8 11 12	52 58 45 56 41 NR NR 6 14 14 17 18	58 63 71 74 67 NR 14 13 15 15 20 21	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92 3.00 3.35	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0 40.8 36.6	2 2 4 7 11 14 18 21 22 26 27 3 6 10	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00 45.00 46.00 39.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0 3899788.0 3899180.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864 104471 117308 89392	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2 20.4 20.7	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.012 0.006 0.006 0.001 0.002 0.003 0.004	No Yes Yes Yes Yes Yes No Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, vFD at 27 Hz. Conducted system checks and changed bag filters, vFD at 27 Hz. Conducted system checks and changed bag filters. VFD at 27 Hz.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/20/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/30/2019 GW 1/3/2020 GW 1/6/2020 GW 1/10/2020 GW 1/13/2020 GW 1/13/2020 GW	TA YA ITA	Yes No Yes			55 59 64 66 45 NR NR 19 18 18 21 25	22 66 70 63 NR 11 11 11 8 11 12 16 20	52 58 45 56 41 NR NR 6 14 14 17 18 23	58 63 71 74 67 NR 14 13 15 15 20 21	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92 3.00 3.35 3.62	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0 40.8 36.6	2 2 4 7 11 14 18 21 22 26 27 3 6 10 13 17	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00 45.00 46.00 39.00 24.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0 3809788.0 3899780.0 3992818.0	83112 0 50812 118235 148125 119831 116984 	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2 20.4 20.7 16.3	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001 0.002 0.003 0.004 0.004	No Yes Yes Yes Yes Yes No Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, Apply at 27 Hz. Conducted system checks and changed bag filters. Adjusted VFD to 33 Hz. Flushed iron sludge/sediment out of bottom of sight glass on EQ holding tank.
12/2/2019 BET 12/4/2019 BET 12/4/2019 GW 12/9/2019 GW 12/13/2019 GW 12/13/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/23/2019 GW 12/26/2019 GW 12/30/2019 GW 1/3/2020 GW 1/10/2020 GW 1/13/2020 GW 1/13/2020 GW 1/17/2020 GW	TA YANGA INTO AN ANTANAN ANTANANAN ANTANAN ANTANAN ANTANANAN ANTANAN ANTAN	Yes No Yes			55 59 64 66 45 NR NR 19 18 18 21 21 25 28	22 66 70 63 NR 11 11 11 2 16 20 21	52 58 45 56 41 NR NR 6 14 14 17 18 23 26	58 63 71 74 67 NR 14 13 15 15 20 21 26 29	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92 3.00 3.35 3.62 3.97	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0 40.8 36.6 33.9 30.9	2 2 4 7 11 14 18 21 22 26 27 3 6 10 13 17 20	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00 45.00 46.00 39.00 24.00 37.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0 3899180.0 3992818.0 4065780.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864 104471 117308 89392 93638 72962	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2 20.4 20.7 16.3 16.9	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001 0.002 0.003 0.004 0.004 0.005	No Yes Yes Yes Yes Yes No Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, vFD at 27 Hz. Conducted system checks and changed bag filters. Conducted system checks and changed bag filters.
12/2/2019 BET 12/4/2019 BET 12/4/2019 GW 12/9/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/23/2019 GW 12/26/2019 GW 12/30/2019 GW 1/3/2020 GW 1/10/2020 GW 1/10/2020 GW 1/17/2020 GW 1/17/2020 GW 1/20/2020 GW	TA YA ITA	Yes No Yes			55 59 64 66 45 NR NR 19 18 18 21 21 25 28 29	22 66 70 63 NR 11 11 11 2 16 20 21 22	52 58 45 56 41 NR NR 6 14 14 17 18 23 26 27	58 63 71 74 67 NR 14 13 15 15 20 21 26 29 30	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92 3.00 3.35 3.62 3.97 5.13	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0 40.8 36.6 33.9 30.9 23.9	2 2 4 7 11 14 18 21 22 26 27 3 6 10 13 17 20 24	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00 45.00 46.00 39.00 24.00 37.00 34.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0 3899180.0 3992818.0 4065780.0 4150180.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864 104471 117308 89392 93638 72962 84400	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2 20.4 20.7 16.3 16.9	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.012 0.006 0.001 0.002 0.003 0.004 0.004 0.001 0.002 0.003 0.004 0.005 0.005	No Yes Yes Yes Yes Yes No Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, when adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, vFD at 27 Hz. Conducted system checks and changed bag filters. Adjusted VFD to 33 Hz. Flushed iron sludge/sediment out of bottom of sight glass on EQ holding tank. Conducted system checks and changed bag filters. Conducted system checks and changed bag filters.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/13/2019 GW 12/20/2019 GW 12/20/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/23/2019 GW 1/2/20/2010 GW 1/13/2020 GW 1/10/2020 GW 1/13/2020 GW 1/13/2020 GW 1/13/2020 GW 1/13/2020 GW 1/20/2020 GW 1/20/2020 GW 1/20/2020 GW 1/20/2020 GW	TA YA ITA	Yes No Yes			55 59 64 66 45 NR NR 19 18 18 21 21 25 28 29 26	22 66 70 63 NR 11 11 11 2 16 20 21 22 24	52 58 45 56 41 NR NR 6 14 14 17 18 23 26 27 25	58 63 71 74 67 NR 14 13 15 15 20 21 26 29 30 28	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92 3.00 3.35 3.62 3.97 5.13 5.75	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0 40.8 36.6 33.9 30.9 23.9 21.3	2 2 4 7 11 14 18 21 22 26 27 3 6 10 13 17 20 24 27	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00 45.00 46.00 39.00 24.00 37.00 34.00 39.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0 3899180.0 3992818.0 4065780.0 4150180.0 4205753.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864 104471 117308 89392 93638 72962 84400 55573	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2 20.4 20.7 16.3 16.9 14.7 12.9	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001 0.002 0.003 0.004 0.004 0.005 0.005	No	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters. VFD at 27 Hz. Conducted system checks and changed bag filters. Conducted system checks and changed bag filters.
12/2/2019 BET 12/4/2019 BET 12/6/2019 GW 12/9/2019 GW 12/13/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/23/2019 GW 1/3/2020 GW 1/10/2020 GW 1/10/2020 GW 1/17/2020 GW 1/12/2020 GW 1/26/2020 GW 1/26/2020 GW 1/26/2020 GW	TA	Yes No Yes			55 59 64 66 45 NR NR 19 18 18 21 21 25 28 29	22 66 70 63 NR 11 11 11 2 16 20 21 22	52 58 45 56 41 NR NR 6 14 14 17 18 23 26 27	58 63 71 74 67 NR 14 13 15 15 20 21 26 29 30	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92 3.00 3.35 3.62 3.97 5.13	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0 40.8 36.6 33.9 30.9 23.9 21.3 18.0	2 2 4 7 11 14 18 21 22 26 27 3 6 10 13 17 20 24 27 31	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00 45.00 46.00 39.00 24.00 37.00 34.00 39.00 36.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0 3899180.0 3992818.0 4065780.0 4150180.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864 104471 117308 89392 93638 72962 84400 55573 66622	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2 20.4 20.7 16.3 16.9 14.7 12.9 11.6	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001 0.002 0.003 0.004 0.004 0.005 0.005	No Yes Yes Yes Yes Yes No Yes	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, when adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, vFD at 27 Hz. Conducted system checks and changed bag filters. Adjusted VFD to 33 Hz. Flushed iron sludge/sediment out of bottom of sight glass on EQ holding tank. Conducted system checks and changed bag filters. Conducted system checks and changed bag filters.
12/2/2019 BET 12/4/2019 BET 12/4/2019 GW 12/9/2019 GW 12/13/2019 GW 12/13/2019 GW 12/16/2019 GW 12/20/2019 GW 12/20/2019 GW 12/23/2019 GW 12/23/2019 GW 11/3/2020 GW 1/10/2020 GW 1/10/2020 GW 1/17/2020 GW 1/20/2020 GW 1/24/2020 GW 1/26/2020 GW 1/26/2020 GW	TA YA ITA	Yes No Yes			55 59 64 66 45 NR NR 19 18 18 21 21 25 28 29 26	22 66 70 63 NR 11 11 11 2 16 20 21 22 24	52 58 45 56 41 NR NR 6 14 14 17 18 23 26 27 25	58 63 71 74 67 NR 14 13 15 15 20 21 26 29 30 28	2.17 2.12 1.95 2.02 NR NR 2.25 2.42 2.37 2.92 3.00 3.35 3.62 3.97 5.13 5.75	26.9 62.0 62.0 62.8 60.6 NR NR 54.4 50.6 54.2 51.8 42.0 40.8 36.6 33.9 30.9 23.9 21.3	2 2 4 7 11 14 18 21 22 26 27 3 6 10 13 17 20 24 27	50	NR NR NR 48.0 40.0 16.00 NR NR 52.00 39.0 49.00 45.00 46.00 39.00 24.00 37.00 34.00 39.00	2685088 2735900 2854135.0 3002260.0 3122091.0 3239075.0 3317372.0 3460145.0 3588009.0 3692480.0 3899180.0 3992818.0 4065780.0 4150180.0 4205753.0	83112 0 50812 118235 148125 119831 116984 78297 142773 858169 127864 104471 117308 89392 93638 72962 84400 55573	28.9 0.0 17.6 27.4 25.7 27.7 20.3 54.4 24.8 22.1 29.6 24.2 20.4 20.7 16.3 16.9 14.7 12.9	0.016 0.001 0.000 0.001 0.002 0.003 0.004 0.004 0.012 0.006 0.006 0.001 0.002 0.003 0.004 0.004 0.005 0.005	No	No N	Bag filters changed prior to system restart. System (PRW-4 and system) restarted at 12:12 following the force main de-scale and purging process. Collected post-bag filter checks after system restart. Conducted system checks, flow into system #2 shutoff PRW-4 due to high level alarm. Changed the bag filters, and adjusted the VFD from 44 Hz to 46 Hz. Conducted system checks, changed bag filters, adjusted VFD to 48 Hz to increase the discharge/effluent flow rate. GWTT communicated that carbon vessels should be backwashed since the differential pressure between P3 and P4 is 50 psi. Conducted system checks, changed bag filters, adjusted VFD from 48 Hz to 49 Hz (49 GPM) at departure. GWTT noted the pressure on the carbon vessels was approaching their maximum limit. Conducted system pressure checks, changed bag filters, adjusted the VFD from 49 Hz to 50 Hz (45 GPM). GWTT noted the pressure on the carbon vessels was approaching their maximum limit. System sampled on 12/17/19. Conducted system pressure checks and changed bag filters and adjusted the VFD from 40 Hz to 47 Hz. Water waste from force main descale process removed from totes off-site by Global Cycle. System shutdown for carbon changeout at 08:00. Spent carbon removed from both vessels and replaced with new virgin carbon. System restarted and requilibrated at 08:00 following carbon changeout and carbon hydration. Conducted system pressure checks, changed bag filters, adjusted the VFD to 23 Hz upon departure. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters, and adjusted VFD. Conducted system checks and changed bag filters. VFD at 27 Hz. Conducted system checks and changed bag filters. Conducted system checks and changed bag filters.

Table 2A- Summary of Groundwater Pump and Treatment System Operating and Maintenance Data - GWTS #1 Barnstable County Fire and Rescue Training Academy
155 Flint Rock Road, Barnstable, MA

RTN 4-26179

		0.1	Influent Bag Fil Pressur			Changeout Pressure (psi)		Changeout Pressure (psi)		INFLUENT				EFFLUENT								
Date	Operator ¹	System Operating on Arrival	Pre	Post	Gauge: P1	Gauge: P2	Gauge: P1	Gauge: P2	6" Influent Tank Fill Rate (min)	Combined Instantaneous Estimated Influent Flow Rate (GPM) ²	Days System Operating	Instant. Effluent Flow Rate (GPM) ⁸	Instantaneous Effluent Flow Rate (GPM) ^{2,9}	Totalizer (Gal)	Total Gallons Treated	Average Effluent Flow Rate (GPM) ¹⁰	Estimated Total PFAs Removal (kg) ³	System Operating on Departure	System Sampled	Comments		
2/4/2020	GWTT	Yes			28	22	26	30	8.00	15.3	4		36.00	4325997	120244	20.9	0.002	Yes	No	Conducted system checks and changed bag filters.		
2/7/2020	GWTT	Yes			26	25	24	28	7.90	15.5	7		38.00	4360208	34211	7.9	0.001	Yes	No	Conducted system checks and changed bag filters.		
2/11/2020	GWTT	Yes			26	25	26	30	11.07	11.1	11		43.00	4399300	39092	6.8	0.001	Yes	No	Conducted system checks and changed bag filters. Backwashed primary LGAC vessel, adjusted transfer pump from 33 Hz to 23 Hz after backwash.		
2/13/2020	GWTT	Yes			9	8	7	9	12.33	9.9	13		42.00	4418200	18900	6.6	0.002	Yes	Yes	Conducted system checks and changed bag filters. Adjusted transfer pump from 33 Hz to 23 Hz, recycled backwash water into GWTS #2 for tr		
2/18/2020	GWTT	Yes			12	6	8	9	16.63	7.4	18		42.00	4454815	36615	5.1	0.002	Yes	No	Conducted system checks and changed bag filters.		
2/21/2020	GWTT	Yes			10	8	9	11	22.67	5.4	21		40.00	4471238	16423	3.8	0.002	Yes	No	Conducted system checks and changed bag filters.		
2/24/2020	GWTT	Yes			15	5	13	15	2.65	46.2	24		44.00	4490425	19187	4.4	0.002	Yes	No	Conducted system checks and changed bag filters. Bag filters packed with significant iron-oixde sediments, influent flow rate into EQ tank signific increased; slug of iron-oxide must have broke through from accumulation in the force main. Adjusted VFD from 23 Hz to 30 Hz.		
2/26/2020	GWTT	Yes			25	10	20	24	2.60	47.1	26		37.00	4519500	29075	10.1	0.005	Yes	No	Conducted system checks and change bag filters. Increase discharge flow through VFD from 30 Hz to 35 Hz. Pressure readings at primary LGAC vessel indicating a need for a backwash.		
2/28/2020	GWTT	Yes			29	10	13	15	2.55	48.0	28		52.00	4556491	36991	12.8	0.007	Yes	No	Conducted system checks and change bag filters. Conducted a backwash on primary LGAC vessel. Initial instantaneous Effluent flow rate was measured at 75 GPM after backwash. Adjusted VFD from 35 Hz to 26 Hz.		
	Totals - Fel	bruary 2020 ¹²								22.9	29		41.6		350738	8.4	0.004					
3/2/2020	GWTT	Yes			21	6	12	14	2.83	43.2	2		46.00	4645525	89034	20.6	0.001	Yes	Yes	Conducted system checks, changed bag filter, pumped water from large exterior tote through GWTS #2. System sampled on 3/3/2020		
3/6/2020	GWTT	Yes			19	10	16	19	3.00	40.8	6		38.00	4723654	78129	13.6	0.002	Yes	No	Conducted system checks, changed bag filters, adjusted VFD from 26 Hz to 30 Hz.		
3/9/2020	GWTT	Yes			25	18	11	15	3.00	40.8	9		51.00	4785425	61771	14.3	0.003	Yes	No	Conducted system checks, changed bag filters, at departure, instantaneous effluent flow rate at 51 gpm (30 Hz).		
3/13/2020	GWTT	Yes			23	8	13	16	3.23	37.9	13		51.00	4898555	113130	19.6	0.005	Yes	No	Conducted system checks, changed bag filters.		
3/16/2020	GWTT	Yes			23	9	14	17	3.75	32.7	16		50.00	4968818	70263	16.3	0.005	Yes	No	Conducted system checks, changed bag filters.		
3/20/2020	GWTT	Yes			25	9	18	21	3.60	34.0	20		42.00	5052480	83662	14.5	0.006	Yes	No	Conducted system checks, changed bag filters, backwashed the primary LGAC vessel, adjusted the VFD from 30 Hz to 25 Hz: 42 GPM. Observed significant iron-oxide sedimentation accumulation in EQ tank.		
3/23/2020	GWTT	Yes	-		17	9	15	17	3.00	40.8	23		48.00	5097785	45305	10.5	0.005	Yes	No	Conducted system checks; had to change the bag filters twice because the accumulated iron-oxide sediment in the EQ tank is getting pulled into the transfer pump affecting total gallons treated. Sight glass on EQ tank was flushed. Adjusted VFD from 25 Hz to 35 Hz.		
3/26/2020	GWTT	Yes			34	17	27	29	3.00	40.8	26		48.00	5163530	65745	15.2	0.008	Yes	No	Conducted system checks, changed bag filters and increased the VFD from 35 Hz to 38 Hz.		
3/30/2020	GWTT	Yes			38	14	34	38	3.27	37.5	30		42.00	5264195	100665	17.5	0.011	Yes	No	Conducted system checks, changed bag filters and increased the VFD from 38 Hz to 40 Hz.		
	Totals - N	March 2020 ¹²								38.7	31		46.2		707704	15.9	0.012					
4/2/2020	GWTT	Yes			34	30	31	35	2.95	41.5	2		51.00	5304740	40545	14.1	0.000	Yes	No	Conducted system checks and changed bag filters.		
4/6/2020	GWTT	Yes			33	33	31	35	3.12	39.3	6		50.00	5354280	49540	8.6	0.001	Yes	No	Conducted system checks and changed bag filters. Transfer pump VFD at 40 Hz.		
4/9/2020	GWTT	Yes					15	18	3.47	35.3	8.5		49.00	5413745	59465	16.5	0.002	Yes	No	System shutdown for 2-4 hours at 7am for vac out of EQ tank and backwash of primary carbon vessel. Global removed 2,989 gallons of iron-oxide water mixture from EQ tank and exterior totes. Conducted system checks and changed bag filters. Adjusted VFD from 40 Hz (74 gpm) to 28 Hz (49 gpm).		
4/13/2020	GWTT	Yes			16	10	11	15	3.92	31.3	12.5		44.00	5497360	83615	14.5	0.002	Yes	No	Conducted system checks and changed bag filters		
4/16/2020	GWTT	Yes			18	15	15	19	4.32	28.4	15.5		35.00	5552940	55580	12.9	0.003	Yes	No	Conducted system checks and changed bag filters		
4/20/2020	GWTT	Yes			19	14	19	23	5.00	24.5	19.5		30.00	5620048	67108	11.7	0.003	Yes	No	Conducted system checks and channed has filters, adjusted VED from 28 Hz to 32 Hz to allow higher pressure/flow through has filters to help with iron.		
4/24/2020	GWTT	Yes			26	21	26	30	5.25	23.3	23.5		30.00	5679610	59562	10.3	0.003	Yes	No			
4/27/2020	GWTT	Yes			30	28	30	34	6.37	19.2	26.5		28.00	5723132	43522	10.1	0.003	Yes	Yes			
	Totals - A	April 2020 ¹²								30.4	29.5		39.6		458937	10.8	0.004					
													1									

2. Prior to November 2019, the instantaneous Influent (INF) and effluent (EFF) flow rates are calculated based on the cross-sectional volume per vertical foot of the influent tank and the measured/timed filling (INF) rate or draining (EFF) of the tank. The diameter of the influent tank is approximately 78 inches. The cross-sectional volume of the tank is approximately 33.1 cubic feet per vertical linear foot. Therefore the flow rate calculation factor is approximately 122.5 gallons per 6 inches. Since 11/7/2019 (following the replacement of the effluent totalizer, ONLY INF flow rates (from PRW-4) are calculated based on an approximation. This Combined Influent flow rate represents the combined flow within both force main pipes from recovery well PRW-4.

3. Prior to November 2019 the total mass of PFAS removed is calculated based on the calculated based on the calculated influent flow rate, the number of days the system has been operating, and the average total Influent PFAs concentration for the month. Since November 2019, the total mass of PFAS removed is

calculated based on the effluent flow rate.
4. NA or -- Not Applicable.

5. NR - Not Reported

6. As of April 1, 2019; the system's O&M data reporting was changed to include the differential pressure readings from the bag filter unit's pressure gauges before and after the bag filters are changed/replaced, if applicable.

7. Prior to November 2019, the average influent flow rate could not reliably be calculated/measured from September to (most of) October due to a blockage in the site glass on the EQ tank from accumulated iron-oxide precipitates in the bottom of the tank. The iron-oxide precipitates were removed from the EQ tank on Oct. 28, 2019.

8. Following the separation of the two force mains and the installation of GWTPS #2 on November 7, 2019, Instantaneous influent flow rates are estimated by approximating 50% of the Combined Instantaneou Influent flow rate values.

9. Instantaneous Effluent Flow Rate is recorded as the instantaneous flow rate as calculated or indicated from the totalizer flow meter on the system's effluent discharge piping - reading is collected after bag filter change and/or backwashing.

10. The Average effluent flow rate is calculated from the net gallons (Total Gallons Treated) obtained from the system's effluent totalizer flow meter and days that the system was in operation.

11. Prior to Nov. 7, 2019, calculated average effluent flow rates and the estimated PFAS removed total were calculated based on the reported totalizer flow meter readings on the effluent discharge piping were not reliable at flow rates less than 40 GPM.

Therefore the data are shaded to indicate that they are approximations only and for this reason the July through October data are also considered approximates.

12. As of September 2019, the "Totals" shown (from left to right) include the Average Instantaneous Influent Flow Rate, Total Days of System Operation, Average Instantaneous Effluent Flow Rate, Total Callons Treated, Average Net Effluent Flow Rate, and Estimated PFAS Removed for the respective monthly reporting period. Running average values shown for the effluent Flow Rate, and Estimated PFAS Removed for the respective monthly reporting period.

March Marc			System	Days	Transfer Pump Pres. (psi)	Pre-Filter Differential P	Changeout ressure (psi) ²		r Changeout Pressure (psi)	Carbon Pre-chang	vessels. ge out (psi)	Carbon Post-chang		Instantaneous Estimated INFLUENT ⁷		EFFLL	JENT		Estimated	System Operating	System	
Control Cont	Date	Operator'	Operating on Arrival	System Operating		Gauge: P2	Gauge: P3	Gauge: P2	Gauge: P3	Gauge: P4	Gauge: P5	Gauge: P4	Gauge: P5	Flow Rate	Totalizer (Gal)	Flow Rate	Gallons	Effluent Flow	Total PFAs Removal (kg)	on		Comments
The color The	11/11/2019	GWTT	Yes	1	38	0	0	0	0	<2	0	2	2	12.56	416900	(01 111)	House	rate (Grivi)	0.00032	Yes	No	Influent flow stream from PRW-4 split and started system #2. Conducted system checks, changed bag filters after initial flush.
No. 1	11/15/2019	GWTT	Yes	4	40	24	2	5	2	2	2	2	2	34.00	451645	34.00	34745.0	8.043	0.0008	Yes	Yes	Conducted system pressure checks and changed the bag filters. System shutdown temporarily to calculate influent flow rate at GWTPS #1. Collected system startup samples on 11/12/19 and 11/15/19.
Control Cont	11/18/2019	GWTT	Yes	7	-	32	2	6	6	2	2	4	4	44.00	491280	33.00	39635.0	9.175	0.0016	Yes	No	Conducted system pressure checks and changed the bag filters. System shutdown temporarily to calculate influent flow rate at GWTPS #1.
Property Property	11/22/2019	GWTT	Yes	11	40	31	4	7	7	4	4	6	5	12.50	549022	34.00	57742.0	10.025	0.0028	Yes	No	
No. Control Control								7											1			
No. West W			4		40	18	6	8	8	3	3	4	4		649150					Yes	No	Conducted system pressure checks and changed the day filters.
No. 10.	Total	J WOVERNEON	1					T							686500		_	_	0.0040	No	Yes	System shutdown at 10:00 for force main de-scale process; system locked out and tagged out.
Part					40			7	7			4	4	22.70		30.00			0.00000			
Property Property	12/6/2019	GWTT	No	4	35	**		14	13			10	8	25.0	707866	47.00	21166.0	7.349	0.00029	Yes	No	GWTT observed a high amount of solids floating in the EO tank and pumped down the EO tank and observed significant iron sediment sludge on the bottom of the tank. GWTT notified BETA that they would raise the floats in EO tank to help lessen the agitation of the sludge and carryover into the bag filters. System was on high level alarm and continued to shutoff of PRW-4, which shut off system #1 due to significant iron oxide sediment
Section Process Proc										7			8									
Property Property								_					7									
											-											
Part					42	33	14	20	20	10	4	18	6.00									
See See					20	20		10		14	 4	10	7									
Process Proc											-		/									
No. No.	12/30/2019	GWTT	Yes	26	38	38	13	22	22	12	5	20	7	24.00	1320824	40.00	111004.0		0.00503	Yes	No	
Section Sect				27		l								24.49								Conducted and the short of the second base 6th and
Property Property				3							4 6		0	20.00								
No. 1																			1			
1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.				13							6	6	8				_					
Process of the content of the cont	1/17/2020	GWTT	Yes	17		28	16	20	20	15	6	18	7	16.94	1750933	41.00	76093.0	13.2	0.00321	Yes	No	Conducted system checks, changed bag filters.
Process Proc								1					7								No	
Part								+		6		_	-			_			1			
Property Column Property C								_		7		9				46.00	_	***				
Part			2020 ⁶		30	10	10	12	12	,			<u> </u>		1702030	44				103	140	
Part	2/4/2020	GWTT	Yes	4	2	18	10	12	12	9	8	8	7	7.66	2000333	46.00		6.6	0.00053	Yes	No	Conducted system checks, changed bag filters.
Part	2/7/2020		Yes		36	14		12	11	8	7	8	6							Yes	No	
## Part								_		,			8									
27/1/200 CMT								1			-								1			
2-72-72-72-72-72-72-72-72-72-72-72-72-72										-		10	8	1								
Part	2/24/2020	GWTT	Yes	24	37	43	5	16	16	2	2	13	7	23.11	2108080	47.00	14026	3.2	0.00156	Yes	Yes	Conducted system checks, changed bag filters. Bag filters packed with significant iron-oixde sediments, influent flow rate into EQ tank significantly
Part							6	ļ		6		1	8						ļ			
Table February 2007 1/2										5												Conducted system checks, changed bag filters. Approximately 6 inch of iron-oxide sludge has accumulated on bottom of EQ tank; control float
27/2000 GVTT Ves 2 36 35 10 15 15 9 5 10 11 216 224900 8.00 8075 117 0.00078 Ves Ves Conducted system checks, changed bag filters, glyshem spliters of 37/2000 GVTT Ves 6 37 25 10 16 15 8 8 12 10 204 2215739 4.00 66379 116 0.00045 Ves No Conducted system checks, changed bag filters. System shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from exterior total strough system. System Shauldown temporarily to pump baskwarh water from					**		-			_	_	1	-									switches were raised to reduce disruption of settled sludge.
3/7/2002 CAVIT Ves 7 3 7 3 7 9 10 10 7 6 5 14 10 204 23/6315 4 4 4 4 5 24 24 2 1 2 1 2 1 2 4 2 3 4 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 2 3 4 4 4 4 4 4 4 4 4				2	36	35	10	15	15	9	5	10	11		2249000		T			Yes	Yes	Conducted system checks, changed bag filters. Backwashed primary LGAC vessel, vaccumed the iron-oxide sludge out of the EQ tank, and into 55-gaddrums on site; water from the drum can be decanted back through the system. System sampled on 3/3/2020.
3/13/2020 GWTT Ves 13 38 37 9 20 20 8 5 18 10 18.9 2476035 42.00 19720 19.0 0.00518 Ves No Conducted system checks, changed bag filters conducted system checks and changed bag filters. 41/6/2020 GWTT	3/6/2020	GWTT	Yes	6	37	25	10	16	15	8	8	12	10	20.4	2315739	47.00	66739	11.6	0.00145	Yes	No	Conducted system checks, changed bag filters. System shutdown temporarily to pump backwash water from exterior totes through system.
3/16/2000 GWTT	3/9/2020	GWTT	Yes	9	37	30	9	16	16	7	6.5	14	10	20.4	2366315	44.00	50576	11.7	0.00220	Yes	No	Conducted system checks, changed bag filters.
3/20/2020 GWTT Yes 20 38 28 17 19 19 10 7 17 10 17.0 2615618 41.00 70760 12.3 0.00514 Yes No Conducted system checks, changed bag filters. Observed significant iron-oxide accumulation in EQ tank. 3/22/2020 GWTT Yes 23 38 26 16 21 20 14 8.5 18 10 20.4 2663514 41.00 27753 6.2 0.00337 Yes No Conducted system checks, changed bag filters. 3/20/2020 GWTT Yes 30 46 44 5 24 24 2 1 20 9 18.8 2721065 37.00 57551 10.0 0.000627 Yes No Conducted system checks, changed bag filters. 3/20/2020 GWTT Yes 30 46 44 5 24 24 2 1 20 9 18.8 2721065 37.00 57551 10.0 0.000627 Yes No Conducted system checks, changed bag filters. 3/20/2020 GWTT Yes 6 42.5 42 12 27 27 10 3 25 6 19.7 2833388 25.00 64825 11.3 0.000849 Yes No Conducted system checks, changed bag filters. 3/20/2020 GWTT Yes 6 42.5 42 12 27 27 10 3 25 6 19.7 2833388 25.00 64825 11.3 0.000859 Yes No Conducted system checks, changed bag filters. 3/20/2020 GWTT Yes 6 42.5 42 12 27 27 10 3 25 6 19.7 2833388 26.00 64825 11.3 0.000859 Yes No Conducted system checks, changed bag filters. 3/20/2020 GWTT Yes 8.5 39 9 8 7 6.5 7 6.5 17.7 2903750 39.00 70382 19.6 0.00097 Yes No Conducted system checks, changed bag filters. 3/20/2020 GWTT Yes 12.5 39 24.5 7 10 9 4 5 8 6.0 15.6 3004475 38.00 10725 17.5 0.00075 Yes No No Conducted system checks and changed bag filters. Lowered transfer pump 'off control' float in EQ holding tank to allow longer run time and less System checks and changed bag filters. Lowered transfer pump 'off control' float in EQ holding tank to allow longer run time and less System checks and changed bag filters. Collected system checks and changed bag filters. Collected sy		GWTT	Yes	13	38	37	9	20	20	8	5	18	10	18.9	2476035	42.00		19.0	1	Yes	No	
A A A A A A A A A A		GWTT	Yes	16	38	29	15	20	20	12	8	18	10	1						Yes	No	
3/26/2020 GWTT Yes 26 38 29 14 20 19 14 8.5 18 10 20.4 2643514 41.00 26.73 6.2 0.00337 Yes No Conducted system checks, changed bag filters. 10/2020 GWTT Yes 2 42 42 13 24 2 1 20 9 18.8 277106 37.00 57.551 10.0 0.00627 Yes No Conducted system checks, changed bag filters. 10/2020 GWTT Yes 2 42 42 13 24 23 10 3 21 5 20.8 2768543 27.00 47478 16.5 0.00041 Yes No Conducted system checks, changed bag filters. 10/2020 GWTT Yes 6 42.5 42 12 27 27 10 3 25 6 19.7 283358 25.00 64825 11.3 0.00085 Yes No Conducted system checks and changed bag filters. 10/2020 GWTT Yes 8.5 39 9 8 7 6.5 7 6.5 17.7 2903750 39.00 70382 19.6 0.0029 Yes No Conducted system checks and changed bag filters. 10/2020 GWTT Yes 8.5 39 9 8 7 6.5 7 6.5 17.7 2903750 39.00 70382 19.6 0.0029 Yes No Conducted system checks and changed bag filters. 10/2020 GWTT Yes 12.5 39 24.5 7 10 9 4 5 8 6.0 15.6 3004475 38.00 100725 17.5 0.00275 Yes No Conducted system checks and changed bag filters. One of the changed bag filters. 10/2020 GWTT Yes 15.5 40 20.8 8 11 10 7 6 6 8 6.0 14.2 3074510 36.00 7035 16.2 0.00316 Yes No Conducted system checks and changed bag filters. One of the changed bag filters. 10/2020 GWTT Yes 15.5 40 20.8 8 11 10 7 6 6 8 6.0 14.2 3074510 36.00 7035 16.2 0.00316 Yes No Conducted system checks and changed bag filters. One of the changed bag							17				7	17							1	1		
3/30/202 GWTT Yes 30 46 44 5 24 24 2 1 20 9 18.8 2721065 37.00 57551 10.0 0.00627 Yes No Conducted system checks, changed bag filters.												1							1			
Totals - March 2020* 31																						
A/A/2020 GWTT Yes 6 42.5 42 12 27 27 10 3 25 6 19.7 2833368 25.00 64825 11.3 0.00085 Yes No Conducted system checks and changed bag filters.						· · · · ·					<u> </u>											
4/6/2020 GWTT Yes 6 42.5 42 12 27 27 10 3 25 6 19.7 283368 25.00 64825 11.3 0.0085 Yes No Conducted system checks and changed bag filters. 4/9/2020 GWTT Yes 8.5 39 9 8 7 6.5 7 6.5 17.7 2903750 39.00 70382 19.6 0.00209 Yes No Bystem shutdown for 2-4 hours at 7am for vac out of EQ holding tank and backwash of primary carbon vessel. Conducted system checks and changed bag filters. 4/13/2020 GWTT Yes 12.5 39 24.5 7 10 9 4 5 8 6.0 15.6 3004475 38.00 100725 17.5 0.00275 Yes No Conducted system checks and changed bag filters. Lowered transfer pump "off control" float in EQ holding tank to allow longer run time and less cycling. 4/16/2020 GWTT Yes 15.5 40 20.8 8 11 10 7 6 8 6 6.0 14.2 3074510 36.00 70035 16.2 0.00316 Yes No Conducted system checks and changed bag filters, pumped backwash water from exterior totes into (system #2) holding tank. 14/20/2020 GWTT Yes 19.5 40 25 8 11 10 6 5 9 6.0 12.3 3156813 37.00 82303 14.3 0.00350 Yes No Conducted system checks and changed bag filters. Lowered transfer pump "off control" float in EQ holding tank to allow longer run time and less cycling. 4/2/2020 GWTT Yes 23.5 42 26 10 15 14 7 5 10 6.0 11.7 3225480 33.00 68667 11.9 0.00357 Yes No Conducted system checks and changed bag filters. 4/2/2020 GWTT Yes 23.5 42 26 10 15 14 7 5 10 6.0 9.6 3271810 33.00 46330 10.7 0.00357 Yes Yes Conducted system checks and changed bag filters. Collected system samples on 4/28/2020.	4/2/2020	GWTT	Yes	2	42	42	13	24	23	10	3	21	5	20.8	2768543	27.00	47478	16.5	0.00041	Yes	No	
Affiliary Affi							12					25										Conducted system checks and changed bag filters. System shutdown for 2-4 hours at 7am for vac out of EQ holding tank and backwash of primary carbon vessel. Conducted system checks and change
4/16/2020 GWTT Yes 15.5 40 20.8 8 11 10 7 6 8 6.0 14.2 3074510 36.00 70035 16.2 0.00316 Yes No Conducted system checks and changed bag filters, pumped backwash water from exterior totes into (system #2) holding tank. 4/20/2020 GWTT Yes 19.5 40 25 8 11 10 6 5 9 6.0 12.3 3156813 37.00 82303 14.3 0.00350 Yes No Conducted system checks and changed bag filters. Lowered transfer pump "off control" float in EQ holding tank to allow longer run time and less cycling. 4/24/2020 GWTT Yes 23.5 42 26 10 15 14 7 5 10 6.0 11.7 3225480 33.00 68667 11.9 0.00352 Yes No Conducted system checks and changed bag filters. 4/27/2020 GWTT Yes 26.5 40 21 12 15 14 10 6 12 6.0 9.6 3271810 33.00 46330 10.7 0.00357 Yes Yes Conducted system checks and changed bag filters. Conducted system checks and changed bag filters. Ves Conducted system checks and changed bag filters.							7					8										
4/20/2020 GWTT Yes 19.5 40 25 8 11 10 6 5 9 6.0 12.3 3156813 37.00 82303 14.3 0.00350 Yes No Conducted system checks and changed bag filters. Lowered transfer pump "off control" float in EQ holding tank to allow longer run time and less cycling. 4/24/2020 GWTT Yes 23.5 42 26 10 15 14 7 5 10 6.0 11.7 3225480 33.00 68667 11.9 0.00352 Yes No Conducted system checks and changed bag filters. Conducted system checks and changed bag filters. Conducted system checks and changed bag filters.					40		8		10	7	6	8	6.0						ļ		No	Conducted system checks and changed bag filters, pumped backwash water from exterior totes into (system #2) holding tank.
4/27/2020 GWTT Yes 26.5 40 21 12 15 14 10 6 12 6.0 9.6 3271810 33.00 46330 10.7 0.00357 Yes Yes Conducted system checks and changed bag filters. Collected system samples on 4/28/2020.										6		9										
4/27/2020 GWTT Yes 26.5 40 21 12 15 14 10 6 12 6.0 9.6 3271810 33.00 46330 10.7 0.00357 Yes Yes Conducted system checks and changed bag filters. Collected system samples on 4/28/2020.	4/24/2020	GWTT	Yes	23.5	42	26	10	15	14	7	5	10	6.0	11.7	3225480	33.00	68667	11.9	0.00352	Yes	No	Conducted system checks and changed bag filters.
Totals - April 2020° 29.5 15.2 34 550745 13.0 0.00481					40	21	12	15		10	6								+	1		
	To	tals - April 20	020 ⁶	29.5										15.2		34	550745	13.0	0.00481			

- Notes:

 1. GWTT Groundwater Treatment Technologies

 2. Pressure readings before filter bag changeout or if no changeout was done.

 3. Influent flow is an instantaneous estimate of the flow rate from the submersible Well Pump at PRW-4.

 4. During monthly reporting periods the net gallons are calculated from previous effluent totalizer readings. (Difference between the current totalizer reading).

 5. The Average effluent flow rate is calculated from the net gallons obtained from the system's effluent totalizer reading.

 6. The "Totals" shown (from left to right) include the, Total Days of System Operation, Average instantaneous influent Flow Rate, Average Net Effluent Flow Rate, and Estimated PFAS Removed for the respective monthly reporting period.

 7. Instantaneous influent flow rates are estimated by supproximating 50% of the influent flow rate values calculated from GWPTS #1 (See Table 2A).

 8. Instantaneous effluent flow rate estimated by stopwarch at totalizer meter.

 9. Flow calculated based on gallons marking on EQ tank. Estimated flow rate = 25 GPM (i.e. flow is calculated based on an in-situ observation of flow into the EQ tank, and 100 gallons of groundwater flows into the EQ tank for a 4 minute duration.



Your Project #: BARNSTABLE COUNTY

Site#: 6206

Site Location: BCFRTA Your C.O.C. #: 743101-01-01

Attention: Steven Tebo

Barnstable County 3195 Main Street PO Box 427 Barnstable, MA USA 02630

Report Date: 2020/05/08

Report #: R6168006 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C0A6377 Received: 2020/04/30, 11:55

Sample Matrix: Water # Samples Received: 5

	Date	Date		
Analyses	Quantity Extracted	Analyzed	Laboratory Method	Analytical Method
Low level PFOS and PFOA by SPE/LCMS (1)	5 2020/05/0	5 2020/05/0	5 CAM SOP-00894	EPA 537 m

Remarks:

Bureau Veritas Laboratories are accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by BV Labs are based upon recognized Provincial, Federal or US method compendia such as CCME, MELCC, EPA, APHA.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in BV Labs profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and BV Labs in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement Uncertainty has not been accounted for when stating conformity to the referenced standard.

BV Labs liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. BV Labs has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by BV Labs, unless otherwise agreed in writing. BV Labs is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by BV Labs, results relate to the supplied samples tested.

This Certificate shall not be reproduced except in full, without the written approval of the laboratory.

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

- * RPDs calculated using raw data. The rounding of final results may result in the apparent difference.
- (1) Per- and polyfluoroalkyl substances (PFAS) identified as surrogates on the certificate of analysis represent the extracted internal standard.



Your Project #: BARNSTABLE COUNTY

Site#: 6206

Site Location: BCFRTA
Your C.O.C. #: 743101-01-01

Attention: Steven Tebo

Barnstable County 3195 Main Street PO Box 427 Barnstable, MA USA 02630

Report Date: 2020/05/08

Report #: R6168006 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C0A6377 Received: 2020/04/30, 11:55

Encryption Key

Please direct all questions regarding this Certificate of Analysis to your Project Manager.

Stephanie Pollen, Project Manager Email: Stephanie.Pollen@bvlabs.com Phone# (905)817-5830

BV Labs has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation please refer to the Validation Signature Page.



Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

RESULTS OF ANALYSES OF WATER

BV Labs ID		MNS891			MNS892	L ¯		
Sampling Date		2020/04/28			2020/04/28			
Sampling Date		08:45			09:00			
COC Number		743101-01-01			743101-01-01			
	UNITS	(PRW-4)INFLLUENT	RDL	MDL	SYSTEM#1 MIDPOINT	RDL	MDL	QC Batch
Perfluorinated Compounds								
Perfluorobutanoic acid (PFBA)	ng/L	27	20	4.5	2.9	2.0	0.45	6709927
Perfluoropentanoic acid (PFPeA)	ng/L	84	20	4.8	6.1	2.0	0.48	6709927
Perfluorohexanoic acid (PFHxA)	ng/L	110	20	2.6	6.9	2.0	0.26	6709927
Perfluoroheptanoic acid (PFHpA)	ng/L	56	20	3.7	3.4	2.0	0.37	6709927
Perfluorooctanoic acid (PFOA)	ng/L	52	20	2.3	2.7	2.0	0.23	6709927
Perfluorononanoic acid (PFNA)	ng/L	42	20	4.8	2.2	2.0	0.48	6709927
Perfluorodecanoic acid (PFDA)	ng/L	12	20	1.8	0.51	2.0	0.18	6709927
Perfluoroundecanoic acid (PFUnA)	ng/L	51	20	3.8	2.0	2.0	0.38	6709927
Perfluorododecanoic acid (PFDoA)	ng/L	<2.5	20	2.5	<0.25	2.0	0.25	6709927
Perfluorotridecanoic acid (PFTRDA)	ng/L	<3.0	20	3.0	<0.30	2.0	0.30	6709927
Perfluorotetradecanoic acid(PFTEDA)	ng/L	<1.6	20	1.6	<0.16	2.0	0.16	6709927
Perfluorobutanesulfonic acid (PFBS)	ng/L	8.5	20	3.7	<0.37	2.0	0.37	6709927
Perfluoropentanesulfonic acid PFPes	ng/L	14	20	2.8	0.74	2.0	0.28	6709927
Perfluorohexanesulfonic acid(PFHxS)	ng/L	210	20	3.3	10	2.0	0.33	6709927
Perfluoroheptanesulfonic acid PFHpS	ng/L	6.5	20	6.3	<0.63	2.0	0.63	6709927
Perfluorooctanesulfonic acid (PFOS)	ng/L	1900	200	43	86	20	4.3	6709927
Perfluorononanesulfonic acid (PFNS)	ng/L	<5.5	20	5.5	<0.55	2.0	0.55	6709927
Perfluorodecanesulfonic acid (PFDS)	ng/L	<3.6	20	3.6	<0.36	2.0	0.36	6709927
Perfluorooctane Sulfonamide (PFOSA)	ng/L	<3.1	40	3.1	<0.31	4.0	0.31	6709927
6:2 Fluorotelomer sulfonic acid	ng/L	160	40	4.3	8.7	4.0	0.43	6709927
8:2 Fluorotelomer sulfonic acid	ng/L	190	40	4.7	11	4.0	0.47	6709927
Surrogate Recovery (%)								
13C2-6:2-Fluorotelomersulfonic Acid	%	90	N/A	N/A	94	N/A	N/A	6709927
13C2-8:2-Fluorotelomersulfonic Acid	%	91	N/A	N/A	90	N/A	N/A	6709927
13C2-Perfluorodecanoic acid	%	91	N/A	N/A	89	N/A	N/A	6709927
13C2-Perfluorododecanoic acid	%	91	N/A	N/A	85	N/A	N/A	6709927
13C2-Perfluorohexanoic acid	%	100	N/A	N/A	98	N/A	N/A	6709927
13C2-perfluorotetradecanoic acid	%	77	N/A	N/A	70	N/A	N/A	6709927
13C2-Perfluoroundecanoic acid	%	93	N/A	N/A	88	N/A	N/A	6709927
13C3-Perfluorobutanesulfonic acid	%	96	N/A	N/A	101	N/A	N/A	6709927
13C4-Perfluorobutanoic acid	%	98	N/A	N/A	94	N/A	N/A	6709927
13C4-Perfluoroheptanoic acid	%	99	N/A	_	96	N/A	N/A	6709927
13C4-Perfluorooctanesulfonic acid	%	101	N/A	N/A	90	N/A	N/A	6709927
RDL = Reportable Detection Limit								
QC Batch = Quality Control Batch								
N/A = Not Applicable								



Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

RESULTS OF ANALYSES OF WATER

BV Labs ID		MNS891			MNS892			
Sampling Date		2020/04/28			2020/04/28			
Sampling Date		08:45			09:00			
COC Number		743101-01-01			743101-01-01			
	UNITS	(PRW-4)INFLLUENT	RDL	MDL	SYSTEM#1 MIDPOINT	RDL	MDL	QC Batch
13C4 Daufly avanatamaia asid								
13C4-Perfluorooctanoic acid	%	95	N/A	N/A	95	N/A	N/A	6709927
13C5-Perfluorononanoic acid	% %	95 93		N/A N/A	95 94	N/A N/A		6709927 6709927
			N/A				N/A	
13C5-Perfluorononanoic acid	%	93	N/A	N/A N/A	94	N/A	N/A N/A	6709927

RDL = Reportable Detection Limit QC Batch = Quality Control Batch



Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

RESULTS OF ANALYSES OF WATER

			T			ı — —	
BV Labs ID		MNS893	MNS894	MNS895			
Sampling Date		2020/04/28	2020/04/28	2020/04/28			
		09:15	09:30	09:45			
COC Number	LINUTC	743101-01-01	743101-01-01	743101-01-01	201	2451	00.0-1-
	UNITS	SYSTEM#1 EFFLUENT	SYSTEM#2 MIDPOINT	SYSTEM#2 EFFLUENT	KDL	MDL	QC Batcl
Perfluorinated Compounds							
Perfluorobutanoic acid (PFBA)	ng/L	<0.45	3.9	<0.45	2.0	0.45	6709927
Perfluoropentanoic acid (PFPeA)	ng/L	<0.48	6.1	<0.48	2.0	0.48	6709927
Perfluorohexanoic acid (PFHxA)	ng/L	0.95	5.7	<0.26	2.0	0.26	6709927
Perfluoroheptanoic acid (PFHpA)	ng/L	<0.37	3.0	<0.37	2.0	0.37	6709927
Perfluorooctanoic acid (PFOA)	ng/L	<0.23	2.2	<0.23	2.0	0.23	6709927
Perfluorononanoic acid (PFNA)	ng/L	<0.48	1.7	<0.48	2.0	0.48	6709927
Perfluorodecanoic acid (PFDA)	ng/L	<0.18	0.27	<0.18	2.0	0.18	6709927
Perfluoroundecanoic acid (PFUnA)	ng/L	<0.38	0.78	<0.38	2.0	0.38	6709927
Perfluorododecanoic acid (PFDoA)	ng/L	<0.25	<0.25	<0.25	2.0	0.25	6709927
Perfluorotridecanoic acid (PFTRDA)	ng/L	<0.30	<0.30	<0.30	2.0	0.30	6709927
Perfluorotetradecanoic acid(PFTEDA)	ng/L	<0.16	<0.16	<0.16	2.0	0.16	6709927
Perfluorobutanesulfonic acid (PFBS)	ng/L	<0.37	<0.37	<0.37	2.0	0.37	6709927
Perfluoropentanesulfonic acid PFPes	ng/L	<0.28	0.56	<0.28	2.0	0.28	6709927
Perfluorohexanesulfonic acid(PFHxS)	ng/L	<0.33	9.7	<0.33	2.0	0.33	6709927
Perfluoroheptanesulfonic acid PFHpS	ng/L	<0.63	<0.63	<0.63	2.0	0.63	6709927
Perfluorooctanesulfonic acid (PFOS)	ng/L	<0.43	64	0.47	2.0	0.43	6709927
Perfluorononanesulfonic acid (PFNS)	ng/L	<0.55	<0.55	<0.55	2.0	0.55	6709927
Perfluorodecanesulfonic acid (PFDS)	ng/L	<0.36	<0.36	<0.36	2.0	0.36	6709927
Perfluorooctane Sulfonamide (PFOSA)	ng/L	<0.31	<0.31	<0.31	4.0	0.31	6709927
6:2 Fluorotelomer sulfonic acid	ng/L	<0.43	7.9	<0.43	4.0	0.43	6709927
8:2 Fluorotelomer sulfonic acid	ng/L	<0.47	6.9	<0.47	4.0	0.47	6709927
Surrogate Recovery (%)							
13C2-6:2-Fluorotelomersulfonic Acid	%	98	77	82	N/A	N/A	6709927
13C2-8:2-Fluorotelomersulfonic Acid	%	94	73	84	N/A	N/A	6709927
13C2-Perfluorodecanoic acid	%	79	73	75	N/A	N/A	6709927
13C2-Perfluorododecanoic acid	%	72	66	70	N/A	N/A	6709927
13C2-Perfluorohexanoic acid	%	86	76	81	N/A	N/A	6709927
13C2-perfluorotetradecanoic acid	%	50	63	72	N/A	N/A	6709927
13C2-Perfluoroundecanoic acid	%	77	70	75	N/A	N/A	6709927
13C3-Perfluorobutanesulfonic acid	%	93	90	91	N/A	N/A	6709927
13C4-Perfluorobutanoic acid	%	79	80	78	N/A	N/A	6709927
13C4-Perfluoroheptanoic acid	%	85	77	79	N/A	N/A	6709927
13C4-Perfluorooctanesulfonic acid	%	90	87	92	N/A	N/A	6709927
RDL = Reportable Detection Limit			1				

QC Batch = Quality Control Batch



Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

RESULTS OF ANALYSES OF WATER

BV Labs ID		MNS893	MNS894	MNS895			
Sampling Date		2020/04/28	2020/04/28	2020/04/28			
		09:15	09:30	09:45			
COC Number		743101-01-01	743101-01-01	743101-01-01			
	UNITS	SYSTEM#1 EFFLUENT	SYSTEM#2 MIDPOINT	SYSTEM#2 EFFLUENT	RDL	MDL	QC Batch
13C4-Perfluorooctanoic acid	%	83	77	77	N/A	N/A	6709927
13C4-Perfluorooctanoic acid 13C5-Perfluorononanoic acid	% %	83 84	77 76	77 79	•	N/A N/A	6709927 6709927
					N/A		
13C5-Perfluorononanoic acid	%	84	76	79	N/A N/A	N/A	6709927

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



Report Date: 2020/05/08

Barnstable County

Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

TEST SUMMARY

BV Labs ID: MNS891

Sample ID: (PRW-4)INFLLUENT

Matrix: Water Collected: Shipped:

2020/04/28

Received:

2020/04/30

Test Description Instrumentation Batch Extracted Date Analyzed Analyst Low level PFOS and PFOA by SPE/LCMS 2020/05/05 2020/05/05 **LCMS** 6709927 Janet Dalisay

BV Labs ID: MNS892

Sample ID: SYSTEM#1 MIDPOINT

Matrix: Water Collected: 2020/04/28

Shipped:

Received: 2020/04/30

Test Description Instrumentation **Batch** Extracted **Date Analyzed** Analyst Low level PFOS and PFOA by SPE/LCMS 6709927 2020/05/05 2020/05/05 Janet Dalisay **LCMS**

BV Labs ID: MNS893

Sample ID: SYSTEM#1 EFFLUENT Matrix:

Water

Collected: 2020/04/28

Shipped:

Received: 2020/04/30

Test Description Instrumentation Batch **Extracted Date Analyzed** Analyst Low level PFOS and PFOA by SPE/LCMS **LCMS** 6709927 2020/05/05 2020/05/05 Janet Dalisay

BV Labs ID: MNS894

Sample ID: SYSTEM#2 MIDPOINT

Matrix: Water Collected: 2020/04/28

Shipped:

Received: 2020/04/30

Test Description Instrumentation **Batch Extracted Date Analyzed** Analyst Low level PFOS and PFOA by SPE/LCMS 2020/05/05 **LCMS** 6709927 2020/05/05 Janet Dalisay

BV Labs ID: MNS895

Sample ID: SYSTEM#2 EFFLUENT

Matrix: Water Collected: Shipped:

2020/04/28

Received: 2020/04/30

Test Description Instrumentation Batch Extracted **Date Analyzed Analyst** Low level PFOS and PFOA by SPE/LCMS 2020/05/05 6709927 2020/05/05 Janet Dalisay **LCMS**



Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

GENERAL COMMENTS

Sample MNS891 [(PRW-4)INFLLUENT]: Per- and polyfluoroalkyl substances (PFAS): Due to high concentrations of the target analytes, a reduced sample volume was extracted and analyzed. Detection limits were adjusted accordingly.

Sample MNS892 [SYSTEM#1 MIDPOINT]: Per- and polyfluoroalkyl substances (PFAS): Due to high concentrations of the target analytes, a reduced sample volume was extracted and analyzed. Detection limits were adjusted accordingly.

Results relate only to the items tested.



Report Date: 2020/05/08

Barnstable County

Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

QUALITY ASSURANCE REPORT

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	% Recovery	UNITS	QC Limits
6709927	JDA	Spiked Blank	13C2-6:2-Fluorotelomersulfonic Acid	2020/05/05		92	%	50 - 150
			13C2-8:2-Fluorotelomersulfonic Acid	2020/05/05		88	%	50 - 150
			13C2-Perfluorodecanoic acid	2020/05/05		90	%	50 - 150
			13C2-Perfluorododecanoic acid	2020/05/05		85	%	50 - 150
			13C2-Perfluorohexanoic acid	2020/05/05		90	%	50 - 150
			13C2-perfluorotetradecanoic acid	2020/05/05		80	%	50 - 150
			13C2-Perfluoroundecanoic acid	2020/05/05		82	%	50 - 150
			13C3-Perfluorobutanesulfonic acid	2020/05/05		93	%	50 - 150
			13C4-Perfluorobutanoic acid	2020/05/05		73	%	50 - 150
			13C4-Perfluoroheptanoic acid	2020/05/05		92	%	50 - 150
			13C4-Perfluorooctanesulfonic acid	2020/05/05		89	%	50 - 150
			13C4-Perfluorooctanoic acid	2020/05/05		84	%	50 - 150
			13C5-Perfluorononanoic acid	2020/05/05		91	%	50 - 150
			13C5-Perfluoropentanoic acid	2020/05/05		89	%	50 - 150
			13C8-Perfluorooctane Sulfonamide	2020/05/05		54	%	20 - 130
			1802-Perfluorohexanesulfonic acid	2020/05/05		92	%	50 - 150
			Perfluorobutanoic acid (PFBA)	2020/05/05		96	%	70 - 130
			Perfluoropentanoic acid (PFPeA)	2020/05/05		93	%	70 - 130
			Perfluorohexanoic acid (PFHxA)	2020/05/05		92	%	70 - 130
			Perfluoroheptanoic acid (PFHpA)	2020/05/05		96	%	70 - 130
			Perfluorooctanoic acid (PFOA)	2020/05/05		91	%	70 - 130
			Perfluorononanoic acid (PFNA)	2020/05/05		95	%	70 - 130
			Perfluorodecanoic acid (PFDA)	2020/05/05		91	%	70 - 130
			Perfluoroundecanoic acid (PFUnA)	2020/05/05		93	%	70 - 130
			Perfluorododecanoic acid (PFDoA)	2020/05/05		95	%	70 - 130
			Perfluorotridecanoic acid (PFTRDA)	2020/05/05		91	%	70 - 130
			Perfluorotetradecanoic acid(PFTEDA)	2020/05/05		88	%	70 - 130
			Perfluorobutanesulfonic acid (PFBS)	2020/05/05		93	%	70 - 130
			Perfluoropentanesulfonic acid PFPes	2020/05/05		102	%	70 - 130
			Perfluorohexanesulfonic acid(PFHxS)	2020/05/05		95	%	70 - 130
			Perfluoroheptanesulfonic acid PFHpS	2020/05/05		91	%	70 - 130
			Perfluorooctanesulfonic acid (PFOS)	2020/05/05		94	%	70 - 130
			Perfluorononanesulfonic acid (PFNS)	2020/05/05		89	%	70 - 130
			Perfluorodecanesulfonic acid (PFDS)	2020/05/05		88	%	70 - 130
			Perfluorooctane Sulfonamide (PFOSA)	2020/05/05		93	%	70 - 130
			6:2 Fluorotelomer sulfonic acid	2020/05/05		91	%	70 - 130
			8:2 Fluorotelomer sulfonic acid	2020/05/05		90	%	70 - 130
6709927	JDA	Spiked Blank DUP	13C2-6:2-Fluorotelomersulfonic Acid	2020/05/05		83	%	50 - 150
		•	13C2-8:2-Fluorotelomersulfonic Acid	2020/05/05		84	%	50 - 150
			13C2-Perfluorodecanoic acid	2020/05/05		93	%	50 - 150
			13C2-Perfluorododecanoic acid	2020/05/05		87	%	50 - 150
			13C2-Perfluorohexanoic acid	2020/05/05		92	%	50 - 150
			13C2-perfluorotetradecanoic acid	2020/05/05		83	%	50 - 150
			13C2-Perfluoroundecanoic acid	2020/05/05		80	%	50 - 150
			13C3-Perfluorobutanesulfonic acid	2020/05/05		96	%	50 - 150
			13C4-Perfluorobutanoic acid	2020/05/05		84	%	50 - 150
			13C4-Perfluoroheptanoic acid	2020/05/05		94	%	50 - 150
			13C4-Perfluorooctanesulfonic acid	2020/05/05		92	%	50 - 150
			13C4-Perfluorooctanoic acid	2020/05/05		82	%	50 - 150
			13C5-Perfluorononanoic acid	2020/05/05		93	%	50 - 150
			13C5-Perfluoropentanoic acid	2020/05/05		89	%	50 - 150



Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	% Recovery	UNITS	QC Limits
Dateii		QC 1 ypc	13C8-Perfluorooctane Sulfonamide	2020/05/05	Value	65	%	20 - 130
			1802-Perfluorohexanesulfonic acid	2020/05/05		96	%	50 - 150
			Perfluorobutanoic acid (PFBA)	2020/05/05		100	%	70 - 130
			Perfluoropentanoic acid (PFPeA)	2020/05/05		99	%	70 - 130
			Perfluorohexanoic acid (PFHxA)	2020/05/05		98	%	70 - 130
			Perfluoroheptanoic acid (PFHpA)	2020/05/05		100	%	70 - 130
			Perfluorooctanoic acid (PFOA)	2020/05/05		97	%	70 - 130
			Perfluorononanoic acid (PFNA)	2020/05/05		100	%	70 - 130
			Perfluorodecanoic acid (PFDA)	2020/05/05		98	%	70 - 130
			Perfluoroundecanoic acid (PFUnA)	2020/05/05		97	%	70 - 130
			Perfluorododecanoic acid (PFDoA)	2020/05/05		99	%	70 - 130
			Perfluorotridecanoic acid (PFTRDA)	2020/05/05		97	%	70 - 130
			Perfluorotetradecanoic acid(PFTEDA)	2020/05/05		92	%	70 - 130
			Perfluorobutanesulfonic acid (PFBS)	2020/05/05		98	%	70 - 130
			Perfluoropentanesulfonic acid PFPes	2020/05/05		108	%	70 - 130
			Perfluorohexanesulfonic acid (PFHxS)	2020/05/05		97	%	70 - 130
			Perfluoroheptanesulfonic acid PFHpS	2020/05/05		95	%	70 - 130
			Perfluorooctanesulfonic acid (PFOS)	2020/05/05		100	%	70 - 130
			Perfluorononanesulfonic acid (PFNS)	2020/05/05		94	%	70 - 130
			Perfluorodecanesulfonic acid (PFDS)	2020/05/05		92	% %	70 - 130 70 - 130
			Perfluorooctane Sulfonamide (PFOSA)	2020/05/05		97	% %	70 - 130
			6:2 Fluorotelomer sulfonic acid	2020/05/05		98	% %	70 - 130
			8:2 Fluorotelomer sulfonic acid	2020/05/05		94	% %	70 - 130
6709927	IDA	RPD	Perfluorobutanoic acid (PFBA)	2020/05/05	4.5	94	% %	
6709927	JDA	KPD	• • •	2020/05/05	4.5		% %	30
			Perfluoropentanoic acid (PFPeA)	2020/05/05	5.9 5.9			30
			Perfluorohexanoic acid (PFHxA)				%	30
			Perfluoroheptanoic acid (PFHpA)	2020/05/05	3.8		%	30
			Perfluorooctanoic acid (PFOA)	2020/05/05	5.7		%	30
			Perfluorononanoic acid (PFNA)	2020/05/05	5.1		%	30
			Perfluorodecanoic acid (PFDA)	2020/05/05	7.4		%	30
			Perfluoroundecanoic acid (PFUnA)	2020/05/05	4.1		%	30
			Perfluorododecanoic acid (PFDoA)	2020/05/05	4.1		%	30
			Perfluorotridecanoic acid (PFTRDA)	2020/05/05	6.3		%	30
			Perfluorotetradecanoic acid(PFTEDA)	2020/05/05	4.1		%	30
			Perfluorobutanesulfonic acid (PFBS)	2020/05/05	5.0		%	30
			Perfluoropentanesulfonic acid PFPes	2020/05/05	5.7		%	30
			Perfluorohexanesulfonic acid(PFHxS)	2020/05/05	2.9		%	30
			Perfluoroheptanesulfonic acid PFHpS	2020/05/05	4.7		%	30
			Perfluorooctanesulfonic acid (PFOS)	2020/05/05	6.4		%	30
			Perfluorononanesulfonic acid (PFNS)	2020/05/05	6.2		%	30
			Perfluorodecanesulfonic acid (PFDS)	2020/05/05	5.1		%	30
			Perfluorooctane Sulfonamide (PFOSA)	2020/05/05	5.2		%	30
			6:2 Fluorotelomer sulfonic acid	2020/05/05	7.4		%	30
			8:2 Fluorotelomer sulfonic acid	2020/05/05	3.6		%	30
6709927	JDA	Method Blank	13C2-6:2-Fluorotelomersulfonic Acid	2020/05/05		93	%	50 - 150
			13C2-8:2-Fluorotelomersulfonic Acid	2020/05/05		94	%	50 - 150
			13C2-Perfluorodecanoic acid	2020/05/05		89	%	50 - 150
			13C2-Perfluorododecanoic acid	2020/05/05		88	%	50 - 150
			13C2-Perfluorohexanoic acid	2020/05/05		97	%	50 - 150
			13C2-perfluorotetradecanoic acid	2020/05/05		85	%	50 - 150
			13C2-Perfluoroundecanoic acid	2020/05/05		89	%	50 - 150



Report Date: 2020/05/08

Barnstable County

Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

QUALITY ASSURANCE REPORT(CONT'D)

Init QC Type	Parameter					OC Limita
	13C3-Perfluorobutanesulfonic acid	Date Analyzed 2020/05/05	Value	% Recovery 94	UNITS %	QC Limits 50 - 150
	13C4-Perfluorobutanoic acid	2020/05/05		94	%	50 - 150
						50 - 150
						50 - 150
						50 - 150
						50 - 150
						50 - 150
	·	· ·				20 - 130
						50 - 15
			<0.45	34		30 - 13
	` ,	· ·			•	
	. , , ,				•	
	•				_	
	, ,				٠.	
		· ·			•	
	, ,					
	` ,				•	
	,				_	
					_	
	,					
	• • •				_	
	·				•	
	•				_	
	·				•	
	• • •				_	
	, ,				_	
					•	
	•	• •				
		· ·				
		13C4-Perfluoroheptanoic acid 13C4-Perfluorooctanesulfonic acid 13C4-Perfluorooctanoic acid 13C5-Perfluorononanoic acid 13C5-Perfluoropentanoic acid 13C8-Perfluorobexanesulfonic acid 13C8-Perfluorohexanesulfonic acid Perfluorobutanoic acid (PFBA) Perfluoropentanoic acid (PFBA) Perfluorohexanoic acid (PFPAA) Perfluoroheptanoic acid (PFHAA) Perfluoroheptanoic acid (PFNA) Perfluoronanoic acid (PFNA) Perfluorodecanoic acid (PFNA) Perfluorondecanoic acid (PFDA) Perfluorondecanoic acid (PFDA) Perfluorotridecanoic acid (PFDA) Perfluorotridecanoic acid (PFDA) Perfluorotridecanoic acid (PFTBA) Perfluorotetradecanoic acid (PFTBA) Perfluorobutanesulfonic acid (PFBS) Perfluoropentanesulfonic acid (PFPS) Perfluoroheptanesulfonic acid (PFNS) Perfluorooctanesulfonic acid (PFNS) Perfluorononanesulfonic acid (PFNS) Perfluorodecanesulfonic acid (PFDS) Perfluorodecanesulfonic acid (PFDS) Perfluorodecanesulfonic acid (PFDS) Perfluorooctane Sulfonamide (PFOSA) 6:2 Fluorotelomer sulfonic acid	13C4-Perfluorooctanesulfonic acid 2020/05/05 13C4-Perfluorooctanoic acid 2020/05/05 13C5-Perfluoropentanoic acid 2020/05/05 13C5-Perfluoropentanoic acid 2020/05/05 13C8-Perfluoroctane Sulfonamide 2020/05/05 1802-Perfluorohexanesulfonic acid 2020/05/05 Perfluoropentanoic acid (PFBA) 2020/05/05 Perfluorohexanoic acid (PFPAA) 2020/05/05 Perfluorohexanoic acid (PFPAA) 2020/05/05 Perfluorohexanoic acid (PFHAA) 2020/05/05 Perfluorohexanoic acid (PFHAA) 2020/05/05 Perfluorononanoic acid (PFDA) 2020/05/05 Perfluorooctanoic acid (PFDA) 2020/05/05 Perfluorononanoic acid (PFDA) 2020/05/05 Perfluorononanoic acid (PFDA) 2020/05/05 Perfluorononanoic acid (PFDA) 2020/05/05 Perfluoroteridecanoic acid (PFDA) 2020/05/05 Perfluoroteridecanoic acid (PFDA) 2020/05/05 Perfluorotetridecanoic acid (PFTRDA) 2020/05/05 Perfluorotetradecanoic acid (PFTRDA) 2020/05/05 Perfluoropentanesulfonic acid (PFBS) 2020/05/05 Perfluorohexanesulfonic acid (PFBS) 2020/05/05 Perfluorohexanesulfonic acid (PFHS) 2020/05/05 Perfluorooctanesulfonic acid (PFNS) 2020/05/05 Perfluorooctanesulfonic acid (PFNS) 2020/05/05 Perfluorooctanesulfonic acid (PFDS) 2020/05/05 Perfluorooctane Sulfonamide (PFOSA) 2020/05/05 Perfluorooctane Sulfonamide (PFOSA) 2020/05/05	13C4-Perfluoroctanesulfonic acid 2020/05/05 13C5-Perfluoroctanoic acid 2020/05/05 13C5-Perfluoropentanoic acid 2020/05/05 13C8-Perfluoropentanoic acid 2020/05/05 13C8-Perfluoropentanoic acid 2020/05/05 18O2-Perfluorobexanesulfonic acid 2020/05/05 Perfluorobutanoic acid (PFBA) 2020/05/05 <0.45	13C4-Perfluorooctanesulfonic acid 2020/05/05 95 13C4-Perfluorooctanoic acid 2020/05/05 94 13C5-Perfluoroopentanoic acid 2020/05/05 95 13C5-Perfluoropentanoic acid 2020/05/05 93 13C8-Perfluorobexanesulfonic acid 2020/05/05 80 18O2-Perfluorobexanesulfonic acid 2020/05/05 94 Perfluoropentanoic acid (PFBA) 2020/05/05 <0.45	13C4-Perfluoroctanesulfonic acid 2020/05/05 95 % 13C4-Perfluoroctanoic acid 2020/05/05 94 % 13C5-Perfluorononanoic acid 2020/05/05 95 % 13C8-Perfluoropentanoic acid 2020/05/05 93 % 13C8-Perfluoroctane Sulfonamide 2020/05/05 80 % 18O2-Perfluorobexanesulfonic acid 2020/05/05 94 % Perfluorobutanoic acid (PFBA) 2020/05/05 <0.45

Duplicate: Paired analysis of a separate portion of the same sample. Used to evaluate the variance in the measurement.

Spiked Blank: A blank matrix sample to which a known amount of the analyte, usually from a second source, has been added. Used to evaluate method accuracy.

Method Blank: A blank matrix containing all reagents used in the analytical procedure. Used to identify laboratory contamination.

Surrogate: A pure or isotopically labeled compound whose behavior mirrors the analytes of interest. Used to evaluate extraction efficiency.



Client Project #: BARNSTABLE COUNTY

Site Location: BCFRTA Sampler Initials: MM

VALIDATION SIGNATURE PAGE

The analytical data and all QC contained in this report were reviewed and validated by the following individual(s).

Adam Robinson, Supervisor, LC/MS/MS

BV Labs has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation please refer to the Validation Signature Page.



July, 2020

Mark S. Ells, Town Manager Town of Barnstable 200 Main Street Hyannis, MA 02601

RE: Immediate Response Action Status and Remedial Monitoring Report #41

Barnstable County Fire and Rescue Training Academy

155 South Flint Rock Road Barnstable, Massachusetts DEP Release Tracking No. 4-26179

Project File #6206

Dear Mr. Ells,

As required by the Massachusetts Contingency Plan (MCP) 310 CMR 40.1403(3)(e) and 40.1403(6), BETA Group, Inc.(BETA) is notifying you on behalf of our client, Barnstable County, that an Immediate Response Action (IRA) Status and Remedial Monitoring Report (RMR) No. 38 is being submitted to the Massachusetts Department of Environmental Protection – Bureau of Waste Site Cleanup (MassDEP – BWSC) for the release site referenced as the Barnstable County Fire and Rescue Training Academy (BCFRTA) located at 155 South Flint Rock Road in Barnstable, Massachusetts (the site). This Report summarizes the IRA activities that occurred from April 1 to April 30, 2020.

Pursuant to the Massachusetts Contingency Plan (310 CMR 40.0480), an Initial Site Investigation has been performed at the site. A release of oils and/or hazardous materials has occurred at the site. In August 2016, MassDEP Southeast Regional Office issued a Notice of Responsibility (NOR) to Barnstable County, as current owner and operator of the Barnstable County Fire and Rescue Training Academy (BCFRTA), that the detection of elevated concentrations of poly- and perfluorylalkyl substances (PFAS) in groundwater at the site constituted a release under the MCP. MassDEP issued Release Tracking Number (RTN) 4-26179 to this release. As summarized in the NOR, based on the detected PFAS concentrations in soil and groundwater at the BCFRTA and the inferred groundwater flow, MassDEP determined that the releases of PFAS from the use of aqueous film-forming foam (AFFF) at the BCFRTA is a source of PFAS detected in the Mary Dunn wells.

During the April 2020 reporting period, the treatment system was operable for approximately 30 days. The overall (average) system flow rate and total gallons of groundwater treated are based on the available Effluent flow totalizer readings reported for both systems by the O&M contractor. For the April 2020 reporting period, both systems treated an approximate combined 1.01 million gallons of groundwater from the downgradient recovery well PRW-4 at an average total (of the two systems) effluent flow rate of 23.4 gpm.

Approximately 0.009 kilograms of PFAs were estimated to have been removed from the plume area during this reporting period. PFAs breakthrough into the effluent from the activated carbon treatment system was not observed.

At this time, IRA activities are ongoing. Continuing IRA activities will include operation and monitoring of the on--Site Groundwater Pump and Treatment Systems (GWPTS), including performance sampling of GWPTS, review and evaluation of the on-Site GWPTS operation and maintenance activities as they affect groundwater treatment, and periodic groundwater monitoring. Additional details regarding the continuing IRA activities are included in the IRA Status and RMR No. 41 report document.

The IRA Status and RMR document is available electronically via the searchable sites database of the MassGOV / MassDEP website via the following link:

https://eeaonline.eea.state.ma.us/portal#!/wastesite/4-0026179

If you have any questions or comments, please do not hesitate to contact our office.

Sincerely, BETA Group, Inc.

Roger P. Thibault, P.E., LSP

Senior Environmental Engineer

Copies: Mass Department of Environmental Protection

Southeast Regional Office 20 Riverside Drive

Pyr P. Thelo

Lakeville, MA 02347

Thomas Mckean, Director

Town of Barnstable Health Division

200 Main Street

Hyannis, MA 02601

Hans Keijser, Supervisor

Town of Barnstable Water Supply Division

47 Old Yarmouth Road

Hyannis, MA 02601